

A remote sensing based approach to quantify the impact of fluvial and pluvial flooding



WP6 : Flood mapping, data assimilation and evacuation route modelling

IISc-Bangalore, Bangalore, India
17th September 2019

Mano Muthusamy
Monica Rivas-Casado
Gloria Salmoral
Paul Leinster

Background

- Problem

Currently, there is a lack of knowledge about the modelling and estimation of pluvial flood and its effective management and mitigation.

- Unaccounted in estimation of flood risk and damages
- Implication in emergency flood planning


Using Environment Agency's flood map

Using UAV data and door-to-door survey

- Requirements for high resolution data (e.g. DEM)
- Data integration

- How WP1 objectives can contribute:

- Utilising high resolution data collected from unmanned aerial system (UAS) pre-, during-, and post-flood event
- Identifying different sources of data and applying appropriate integration methods



Ref : Rivas Casado, M.; Irvine, T.; Johnson, S.; Palma, M.; Leinster, P. The Use of Unmanned Aerial Vehicles to Estimate Direct Tangible Losses to Residential Properties from Flood Events: A Case Study of Cockermouth Following the Desmond Storm. Remote Sens. 2018, 10.

Aim and objective


- Aim

To develop a remote sensing based integrated methodology to quantify and compare the impacts of fluvial and pluvial flooding.

- Objectives


- o Identify different sources of data and apply appropriate integration methods to prepare data for a high-resolution DEM based 2D model for the study site.
- o Develop and calibrate the flood model which can simulate both pluvial and fluvial flooding.
- o Compare the flood extent and depth for different land use types between pluvial and fluvial flooding.
- o Estimate the number of residential properties affected by pluvial and fluvial flooding separately using a combination of model results and UAS data.

Study site and selected event





- Population ~ 8800 Households ~ 4000 (2011)
- Multiple floods in recent times
e.g. Three storms in Dec, 2015
- Storm Desmond
 - o 5-6/12/2015
 - o 341 mm of rain in 24 hrs (UK record)
 - o 5200 homes were flooded

Methodology






Results - Calibration




	SSFB	KF
RMSE (m)	0.28	0.69
Percentage error - peak flow	6%	1%


Results – Flood extent



Results – Flood depth



Results – Land use level analysis



Results – Property level analysis

Contribution of pluvial flooding in total flood depth	Number of properties
0 (Fluvial flooding only)	16
1% - 25%	84
26% - 50%	41
51% - 75%	11
76% - 99%	10
100% (Pluvial flooding only)	51
Total	213

Conclusions

- Pluvial flooding can have a significant effect even in a catchment where fluvial flooding is the major cause of the flood damages.
 - Shows that pluvial flooding needs to be taken into account for a comprehensive flood emergency planning.
- The presented study needs to be further improved by collecting more data for more comprehensive calibration of pluvial flood extend and depth.
 - A wider use of UAS in data collections could be the most effective way to do this.
- This will eventually help to develop a better informed emergency flood plan.

Thank you!

Questions?