

Fundamental Challenges and Complexities of Damage Identification from Dynamic Response in Plate Structures

Yousef Lafi A. Alshammari ^{1,2} , Feiyang He ¹, Abdullah Ayed Alrwili ²  and Muhammad Khan ^{1,*} 

¹ Centre for Life-Cycle Engineering and Management, Cranfield University, Bedford MK43 0AL, UK; y.l.alshammari@cranfield.ac.uk (Y.L.A.A.); feiyang.he@cranfield.ac.uk (F.H.)

² Mechanical Engineering Department, Engineering College, Northern Border University, King Fahad Road, Arar 92341, Saudi Arabia; abdullah.alrwili@cranfield.ac.uk

* Correspondence: muhammad.a.khan@cranfield.ac.uk; Tel.: +44-(0)-1234-754788

Abstract: For many years, structural health monitoring (SHM) has held significant importance across diverse engineering sectors. The main aim of SHM is to assess the health status and understand distinct features of structures by analyzing real-time data from physical measurements. The dynamic response (DR) is a significant tool in SHM studies. This response is used primarily to detect variations or damage by examining the vibration signals of DR. Numerous scholarly articles and reviews have discussed the phenomenon and importance of using DR to predict damages in uniform thickness (UT) plate structures. However, previous reviews have predominantly focused on the UT plates, neglecting the equally important varying thickness (VT) plate structures. Given the significance of VT plates, especially for academic researchers, it is essential to compile a comprehensive review that covers the vibration of both the UT and VT cracked plate structures and their identification methods, with a special emphasis on VT plates. VT plates are particularly significant due to their application in critical components of various applications where optimizing the weight, aerodynamics, and dimensions is crucial to meet specific design specifications. Furthermore, this review critically evaluates the damage identification methods, focusing on their accuracy and applicability in real-world applications. This review revealed that current research studies are inadequate in describing crack path identification; they have primarily focused on predicting the quantification of cracks in terms of size or possible location. Identifying the crack path is crucial to avoid catastrophic failures, especially in scenarios where the crack may propagate in critical dimensions of the plate. Therefore, it can be concluded that an accurate analytical and empirical study of crack path and damage identification in these plates would be a novel and significant contribution to the academic field.

Keywords: vibration measurements; dynamic response; cracked plate; intact plate; damage detection; uniform thickness; varying thickness



Citation: Alshammari, Y.L.A.; He, F.; Alrwili, A.A.; Khan, M. Fundamental Challenges and Complexities of Damage Identification from Dynamic Response in Plate Structures. *Appl. Sci.* **2024**, *14*, 8230. <https://doi.org/10.3390/app14188230>

Academic Editors: Luca Lomazzi, Francesco Cadini and Diogo Ribeiro

Received: 18 July 2024

Revised: 26 August 2024

Accepted: 11 September 2024

Published: 12 September 2024



Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

A plate represents a structural component characterized by its three-dimensional solid geometry with a significantly thin thickness in relation to its other dimensions [1]. In various engineering applications [2–4], plates serve to offer structural reinforcement and assist in the distribution of loads and stresses throughout the construction [5].

Over time, plates are subject to extreme events, persistent ambient oscillations, and natural incidents like earthquakes, corrosion, traffic-induced pressures, and material degradation, which cause damage to their microstructure [6]. Cracks can seriously damage structural effectiveness. Even minor damages can disrupt a plate's function, potentially resulting in structural breakdowns [7]. As a result, the consistent evaluation of the plates' performance has become vital to ensure structural robustness and safety [8,9]. In other words, developing methods for early crack detection and accurate localization has become essential for the continuous operation and longevity of machinery and infrastructure [10].

Over the years, SHM and methodologies for identifying damage in plate structures have grown prominently in disciplines such as aerospace, civil, and mechanical engineering [11–13]. Specialists in damage identification have made efforts to develop cost-effective and reliable monitoring methods. Emphasis in their research has been placed on utilizing the DR to determine plate deterioration [14–18]. This technique is effective for detecting hidden damage in a plate’s interior, as evidenced by variations in characteristics such as stiffness detectable through vibration analyses. Additionally, this approach allows for inspections during active operations, reducing the potential downtime and associated expenses [19,20].

Numerous scholarly articles and reviews have been written to explain the phenomenon and significance of using the DR to predict the damages in UT plates [19,21–26]. Nevertheless, despite the significant progress achieved, a research gap still exists in the context of damage detection in VT plates. Plates characterized by a VT hold substantial significance, as they find application in critical components such as aircraft wings, automobile chassis, vessels, buildings, and more, where the optimization of weight, aerodynamics, and dimensions is essential to meet specific design specifications [27].

Additionally, the critical review showed that the current research studies and their findings are insufficient in describing how to identify the crack path. Researchers have rarely studied the crack path in beams in the literature [28,29], and for plates, they only predict the size or potential location of the crack [30–35]. Identifying the crack path direction is crucial for several reasons such as preventing catastrophic failures because it may move in a direction where the size of the plate is critical, helping engineers to design structures that are more resistant to cracking, and can be used to develop methods for repairing and monitoring structures that have cracked.

Addressing these research gaps, therefore, represents an opportunity for further investigation. By doing so, a comprehensive understanding of the challenges and prospects associated with monitoring techniques for detecting damage in VT plates and crack paths can be obtained, which will streamline the processes associated with the inspection of engineering structures, thereby reducing the time, effort, and associated costs.

The subsequent sections of this paper are structured as follows. A general background and the fundamentals of the vibration of plates are presented in Section 2. In Section 3, vibration-based damage identification for cracked plates in forward and inverse research is discussed and reviewed. A general discussion of all sections is presented in Section 4. Conclusions are drawn, and gaps are listed in Section 5.

2. Fundamentals of Plate Structural Vibration

Using DR to identify damage in plate structures relies heavily on a thorough understanding of their vibrational behavior. This section provides an overview of essential plate vibration theories and details how the crack term is formalized to achieve precise vibration characteristics, which is critical for accurate damage identification.

2.1. Plate Theories

The study of plate vibrations began with the development of linear models. These models have gradually progressed to address the complexities of real-world applications. The initial work by Euler and Bernoulli in 1766 and 1789 provided the foundation by modeling plates as two-dimensional membranes. This work led to the derivation of the first differential equations describing the vibrational behavior of thin plates, as illustrated in Equation (1) [36]. These models serve as a reference point for identifying irregularities caused by structural damage.

$$\frac{\partial^2 w}{\partial t^2} = A \frac{\partial^2 w}{\partial x^2} + B \frac{\partial^2 w}{\partial y^2} \quad (1)$$

After that, Lagrange [37] formulated the first true equation governing the free vibration of plates by integrating the effects of bending stiffness into the vibration equations. Navier,

in 1823, further enhanced the theory by considering the molecular structure of the plate. This approach enabled the derivation of a comprehensive differential equation for lateral loading, as shown in Equation (2) [36].

$$D \left(\frac{\partial^4 w}{\partial x^4} + 2 \frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4} \right) = q \quad (2)$$

Later, in 1887, Kirchhoff re-evaluated this equation using an alternative energy method [36]. However, significant developments were made between 1877 and 1945 by Rayleigh [38,39] and Timoshenko [40]. These improvements included the effects of transverse shear deformation and rotary inertia, expanding the usefulness of classical theories to higher frequencies. These led to studies on rectangular plate (RP) vibrations using the Rayleigh–Ritz method (RRM) [41–43].

Subsequent developments came from Reissner (1945) [44] and Mindlin (1951) [45] by introducing the first-order shear deformation theory (FSDT). This theory is used when a shear correction factor is required to reconcile the actual stress state with the assumed normal stress state [46].

Building upon Mindlin’s work, higher-order shear deformation theories (HSDTs) were developed in the 1960s and 1970s. These theories incorporate higher-order terms in the displacement fields, leading to better accuracy for thick plates without the need for a shear correction factor [47–49]. Reddy (1984) [50] made significant contributions in this area by developing a third-order theory that accurately predicted displacements and stresses while ensuring zero transverse shear stress on the plate surfaces.

More recently, Neves et al. (2012) [51] developed a quasi-3D sinusoidal shear deformation theory for functionally graded plates (FGPs) based on Carrera’s unified formulation (CUF). This theory improves the accuracy of static and free vibration analyses by accounting for thickness stretching. Building on these advancements, Ghazwani et al. (2024) [52] further refined these theories, increasing the accuracy of plate analysis, especially for thick and complex structures. This improvement was achieved by enhancing the displacement fields and eliminating the need for shear correction factors.

2.2. Nonlinear Deflection Theory

The concept of nonlinear theory in DR relates to systems displaying nonlinear vibration behaviors in their reactions to external excitation. Such nonlinear systems challenge the principle of superposition, where combining individual inputs does not accurately predict the overall system response; especially when dealing with deflections, approximately one-tenth of a plate’s thickness, structural stiffening occurs, a phenomenon not accounted for by linear theory [53–55].

Nonlinear vibration behaviors have been studied in many research studies [56–72]. However, the pioneering contributions in nonlinear theory include Kirchhoff’s description of plate bending and elongation [73], Von Karman’s publication of the final form of nonlinear differential equations for statically deflected plates with moderate deflections in 1910 [74], and Bromberg and Stoker’s development of nonlinear theories for plane and curved shells while neglecting bending in 1945 [75].

Later, in 1955, Berger [76] simplified a set of equations that explained the significant deformation of plates. Chu and Hermann (1956) [77] employed a perturbation theory to address the nonlinear free vibrations of the RP. Casado-Pascual et al. (2003) [78] introduced a simplified two-state model to explain the nonlinear dynamics of bistable systems. Liu et al. (2013) [79] developed an analytical theory for characterizing nonlinear DR of waveguide-cavity structures. Liu et al. (2017) [80] developed nonlinear theories for laminated plates and casings, highlighting the classical nonlinear large deformation theory. Yang and Xiang (2022) [81] suggested a thorough response function theory, showing microscopic nonlinear dynamic processes in molecular vibrational polaritons.

2.3. Equation of Motion of Cracked Plates

Based on previous plate theories, the governing equations were developed and utilized to comprehend the behavior of plates under various loading conditions and boundary constraints. Leissa [82] and Szilard [37] deeply analyzed the governing equation of the RP in its traditional form. They proposed the governing equation of an intact isotropic and orthotropic RP with the UT and VT based on classical plate theory. Their works serve as a reference point for developing the governing equations to identify irregularities caused by structural damage.

Building upon these works, Israr et al. (2011) [83] developed a governing equation for RP with UT featuring a central crack (a). They utilized the approximate relationship between nominal tensile and bending stresses at the crack location, as shown in Figure 1, to enhance the model's accuracy, as shown in Equation (3). Ismail and Cartmell (2012) [84] extended Israr's work by formulating a governing equation that accounts for a crack inclined at an angle on the top surface of the plate, subjected to bending moments and tension, as shown in Equation (4). Compliance coefficients att , abb , and $abt = atb$ are recognized from Rice and Levy's paper [85]. Meanwhile, the Ctt , Cbb , and $Cbt = Ctb$ coefficients can be found in the paper by Joseph and Erdogan [86].




Figure 1. (a) In-plane forces acting on the plate, and (b) cracked plate deformation and two-sided constraints [83].

$$\begin{aligned}
 & D \left(\frac{\partial^4 w}{\partial x^4} + 2 \frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4} \right) \\
 & = -\rho h \frac{\partial^2 w}{\partial t^2} + n_x \frac{\partial^2 w}{\partial x^2} + P_z + \frac{2aD \left(\frac{\partial^4 w}{\partial y^4} + v \frac{\partial^4 w}{\partial x^2 \partial y^2} \right)}{3 \left(\frac{\alpha_{bt}^\circ}{6} + \alpha_{bb}^\circ \right) (3+v)(1-v)h + 2a} \\
 & \quad - \frac{2a}{(6\alpha_{tb}^\circ + \alpha_{tt}^\circ)(1-v^2)h + 2a} n_{rs} \frac{\partial^2 w}{\partial y^2}
 \end{aligned} \tag{3}$$

$$\begin{aligned}
& D \left(\frac{\partial^4 w}{\partial x^4} + 2 \frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4} \right) \\
&= -\rho h \frac{\partial^2 w}{\partial t^2} + n_x \frac{\partial^2 w}{\partial x^2} + q_z + \frac{aD(1 + \cos 2\beta) \left(\frac{\partial^4 w}{\partial y^4} + v \frac{\partial^4 w}{\partial x^2 \partial y^2} \right)}{3 \left(\frac{\alpha_{bt}}{6} + \alpha_{bb} \right) (3 + v)(1 - v)h + 2a} \\
&- \frac{a(1 + \cos 2\beta)}{(6\alpha_{tb} + \alpha_{tt})(1 - v^2)h + 2a} n_o \frac{\partial^2 w}{\partial y^2} + \frac{2aD \sin 2\beta \left(\frac{\partial^4 w}{\partial x \partial y^3} + v \frac{\partial^4 w}{\partial x^3 \partial y} \right)}{3 \left(\frac{C_{bt}}{6} + C_{bb} \right) (1 + v)h + 2a} \\
&- \frac{2a \sin 2\beta}{(6C_{tb} + C_{tt})(1 + v)h + 2a} n_o \frac{\partial^4 w}{\partial x \partial y}
\end{aligned} \quad (4)$$

Gupta et al. (2018) [27] further expanded this area of study by deriving equations of motion for partially cracked isotropic and FGM plates with both linear and parabolically varying thicknesses (LVT and PVT). They developed the crack terms using the line spring model (LSM) for plates with VT, making them dependent on the plate thickness. Their analysis, based on classical plate theory, assumed that the volumes of the plates with the VT and the UT were identical to enable a comparison of dynamic properties. For simplification, they disregarded the normal stress, shear deformation, and rotary inertia, as shown in Equation (5). Chandrakar et al. (2022) [87] continued this research by focusing on cracked orthotropic plates with VT under different boundary conditions and incorporated crack terms using the LSM. The study also explored the impact of in-plane forces on frequency response by analyzing nonlinearity using multiple scales.

$$\begin{aligned}
& (D_x^*) \frac{\partial^4 w}{\partial x^4} + 2B^* \frac{\partial^4 w}{\partial x^2 \partial y^2} + (D_y^*) \frac{\partial^4 w}{\partial y^4} + 2 \frac{\partial(D_x^*)}{\partial x} \frac{\partial^3 w}{\partial x^3} + 2 \frac{\partial(B^*)}{\partial x} \frac{\partial^3 w}{\partial x \partial y^2} + 2 \frac{\partial(B^*)}{\partial y} \frac{\partial^3 w}{\partial y \partial x^2} + \frac{\partial^2(D_x^*)}{\partial x^2} \frac{\partial^2 w}{\partial x^2} \\
&+ \frac{\partial^2(D_1^*)}{\partial x^2} \frac{\partial^2 w}{\partial y^2} + \frac{\partial^2(D_1^*)}{\partial y^2} \frac{\partial^2 w}{\partial x^2} + \frac{\partial^2(D_y^*)}{\partial y^2} \frac{\partial^2 w}{\partial y^2} + 2 \frac{\partial(D_y^*)}{\partial y} \frac{\partial^3 w}{\partial y^3} + 4 \frac{\partial^2 D_t(x, y)}{\partial x \partial y} \frac{\partial^2 w}{\partial x \partial y} + \rho h(x, y) \frac{\partial^2 w}{\partial t^2} \\
&= N_{x1} \frac{\partial^2 w}{\partial x^2} + P_z + \frac{2a}{3 \left(\frac{\varepsilon_{tb}}{6} + \varepsilon_{bb} \right) + (3 + \nu_x)(1 + \nu_x)h_c + 2a} \times D_y^* \left(\frac{\partial^4 w}{\partial y^4} + \nu_x \frac{\partial^2 w}{\partial x^2 \partial y^2} \right) \\
&- \frac{2a}{(6\varepsilon_{tb} + \varepsilon_{tt})(1 - \nu_x^2)h_c + 2a} N_{y1} \frac{\partial^2 w}{\partial y^2}
\end{aligned} \quad (5)$$

3. Crack Detection in Plates Using Dynamic Response (DR)

In SHM studies, examining the DR is essential for detecting changes or damage in dynamic systems using vibration signal analysis. This analysis aims to identify, locate, and measure any structural damages present. Notably, a crack in a structure increases the flexibility locally, affecting its static and dynamic behaviors. Engineers have worked extensively to understand and model the changes caused by cracks and their effects on the structure's dynamic properties. It is important to mention that most models have been developed to explore changes in DR due to crack damage, addressing a forward problem. However, damage detection through vibration measurements, which is an inverse problem, is challenging and sometimes impractical. This discussion will further explore both forward and inverse problem research, with attention to the VT configurations in the following sections.

3.1. Forward Problem for the DR of the Cracked Plate

Various research initiatives have been conducted to examine changes in the DR of plate structures due to damage caused by cracks, a situation identified as a forward problem. These studies can be systematically divided into two categories, depending on the thickness of the plates being analyzed.

3.1.1. Plate of the Uniform Thickness (UT)

Numerous researchers have focused on studying the dynamic behaviors of UT plates with cracks, developing various analytical approaches. Before the widespread use of the FE method, mathematical techniques were essential for understanding the vibration dynamics of these plates [88].

Early significant contributions to this field, dating back to 1967 by Lynn and Kum-basar [89], involved using Green's function to formulate a Fredholm integral equation of the first kind to analyze vibrations in cracked RP. This equation was designed for mixed edge conditions influenced by the crack's presence. The Krylov and Bogoliubov method was later used to solve this equation, particularly for cases involving narrow cracks and plates with fully supported boundaries. The outcomes of this solution were observed as frequency changes corresponding to different crack sizes. Stahq and Keer (1972) [90] studied the vibrations and stability of cracked RP using dual-series equations, resulting in a second kind of homogeneous Fredholm integral equation. Joseph et al. (1988) used the LSM to analyze part-through cracks in shells under mixed loading, and found that shell curvature minimally affected the stress intensity factors for superficial cracks [91]. Maruyama and Ichinomya (1989) investigated the free vibration dynamics of the RP with straight slits, using holographic interferometry to study the effect of slit dimensions, positions, and angles on natural frequencies and related modal shapes. Their experiments included different slit positions and angles, showing a decrease in natural frequencies with increasing slit dimensions and angles [92]. Liew et al. (1994) [93] aimed to understand the vibration characteristics of cracked RP by employing the domain decomposition method. Their study was divided into two specific cases, cracks originating from the edge and cracks located in the center. Their findings revealed that the presence of cracks reduced the plates' flexural rigidity, resulting in lower vibrational frequencies in both cases. Khadem et al. (2000) [94] created and utilized modified comparison functions to analyze vibrations in the SS, cracked RP. This method provided benefits like not being restricted by specific types of functions, having higher accuracy, and being easier to use compared to eigenfunctions. The researchers used these modified functions to determine the natural frequencies of cracked plates via the RRM, with variations in frequencies based on crack depth, length, and position.

Pia et al. (2002) [95] used the scanning laser vibrometer technique to study the dynamics of damaged CP and successfully identified minor defects through the analysis of modal shapes and frequencies. Wu et al. (2005) [96] utilized the incremental harmonic balance (IHB) method to examine the dynamic instability and nonlinear responses of cracked plates under periodic forces, illustrating instability regions and exploring the effects of different parameters on the instability and nonlinear behaviors of these plates. Salehi-Khojin et al. (2006) [97] used both experimental and analytical techniques to study the effects of patch layers and loading frequencies on the fatigue fracture behaviors of aluminum plates, focusing on variations in key fracture mechanics parameters. In the same year, Israr et al. (2006) [98] presented approximate solutions for plate vibrations related to cracks, developing an analytical equation for the dynamics of edge-loaded plates with various boundary conditions. They later expanded the applications of their research, providing relationship information between forces and moments at crack tips and plate edges, significantly advancing the study of vibrations in plates with partial cracks. Their findings highlighted the impact of cracks on natural frequencies, where the frequency of damaged plate dropped, as shown in Table 1 [7]. In 2011 [83], they introduced a model to

analyze the vibration dynamics of damaged isotropic plates, with the results aligning well with other research in the field.

In addition, Saito et al. (2008) [99] examined the vibration behaviors of cracked cantilevered plates by considering changes in crack location and length, using FEM and the hybrid frequency/time (HFT) method. The study focused on nonlinearity due to crack closing effects, particularly near veerings. The research highlighted the effect of crack location and length on the first 15 natural frequencies, as shown in Figure 2. Natarajan et al. (2011) [100] studied the vibration characteristics of cracked FGM plates by considering various parameters and observed a decrease in natural frequency with increasing temperature gradients, crack lengths, and gradient indices. Huang et al. (2011) [101] used the RRM to analyze vibrations in plates with internal disruptions, introducing functions that accurately represented stress near crack tips and discontinuity across cracks. A 2018 study built on this presented a refined method for analyzing plates with through-cracks, concentrating on how crack parameters influence frequency variations, mode transition, and localization [102]. Soon after, Ismail and Cartmell (2012) [84] explored how crack orientation influenced the base frequency of partially cracked isotropic plates using both analytical and experimental methods. Bose et al. (2013) [103] conducted a comprehensive investigation into the impact of crack orientation and position on the natural frequency of cracked plates by employing the LSM. Their findings unveiled an inverse correlation between the natural frequency and crack length, independent of the plate's boundary constraints. Moreover, for SS or CS plates, an increase in crack angle up to 45 degrees induced a reduction in the natural frequency. Conversely, the natural frequency exhibited an upward trend with increasing crack eccentricity. In 2016, Bose et al. [104] extended their research to include mobility analysis, which provided a deeper understanding of side cracks within the RP. In their analysis, the RRM has demonstrated its effectiveness in providing valuable insights into the dynamics of forced vibration, showing the connections between normalized mobility, crack length ratios, and crack angles. Jung et al. (2014) [105] developed a bending and vibration analysis model for specific microplates, while Khalili et al. (2014) [106] examined the responses of cracked aluminum plates repaired with composite patches. Beigi et al. (2014) [107] conducted a study using the FEM to understand the impact of various crack parameters such as crack orientation, length, and position on plate vibrations. Joshi et al., working from 2014 to 2017 [108–112], extensively used the LSM to explore the effects of cracks on the vibration dynamics of various plate types, highlighting the decline in the base frequency with rising temperatures. Their results shed light on the vibrational changes caused by cracks and the comprehensive impacts of thermal moments and in-plane forces on plates of different materials including isotropic and FGM plates. They also explored the thermal effects on these plates using the modified couple stress theory in later studies [113].

Moreover, Akgoz and Civalek (2015) [114] introduced a novel sinusoidal plate model that was founded on the modified strain gradient theory. Using Hamilton's principle, they derived the governing equations and their associated boundary conditions, enabling a more precise analysis of free vibrations in microplates. Gupta et al., in 2015 and 2016, developed a framework highlighting the influence of microstructure and fiber orientation on vibrational characteristics of different cracked plates [115,116]. Gao et al. (2017) [117] and Ghadiri et al. (2017) [118] analyzed the nonlinear dynamic properties and stability of plates, revealing relationships between different parameters including temperature, crack length, and boundary conditions. Shojaeefard et al. (2017) examined the free vibration of specific FG porous CP under nonlinear thermal loads. In 2018, their study used the FSDT to analyze the vibration of rotating nano/micro-CP made from FG materials [119,120]. Mahinzare et al., in 2017 and 2018, utilized FSDT to investigate the vibration of various rotating CP, focusing on the relationship between variables such as angular velocity, size, and external electric voltage on the vibrational behavior of cracked plates [121,122].

Research by Chouiyakh et al. (2018) [123] and Moradi et al. (2018) [124] presented the Hilbert transform and Mindlin theory to detect and study the characteristics of cracks on plates, focusing on structural deterioration and the impact of load. Gupta et al. (2018) [125]

investigated the damage location effects on the primary frequency of plates in thermal environments, emphasizing temperature and damage-related factors. From 2018 to 2020, Soni et al. [126–131] conducted a series of studies on cracked plates, focusing on vibration analysis and the influence of various factors such as temperature, immersion depth, and internal material length scale. Their research investigated the dynamics of different types of plates with cracks, providing analytical models for submerged, thermally influenced plates, and exploring the influence of crack length and microstructure on frequency. Meanwhile, Mashrouteh et al. (2019) [132] explored the vibration characteristics of a uniquely cracked plate, offering new understandings of frequency responses related to crack angle. Their findings indicate an inverse relationship between crack angle and frequency response, as shown in Figure 3.

Recently, Ranjbaran and Seifi (2020) [133] introduced an analytical approach based on Kirchhoff's theory to investigate the natural vibrational characteristics of isotropic plates with surface or internal cracks, focusing on how various crack and boundary condition parameters affect natural frequencies. They concluded that the presence of internal cracks significantly altered the natural frequencies of a structure compared to surface cracks. Additionally, the longer the crack, the lower the natural frequencies. Dean et al. (2020) [134] utilized a multi-phase field approach to address the initiation of intra-laminar cracking in long fiber-reinforced composites. However, these studies did not offer any models or methodologies for examining buckling and free vibration issues, which are commonly encountered in practical applications. To address this gap, Dean et al. (2021) [135] applied phase-field theory to analyze multi-crack plates using Mindlin plate theory, where each layer contains a crack that extends through the layer's thickness according to the angle-ply orientation, but does not penetrate the entire plate thickness. In developing this theory, multiple phase-field variables were introduced, with each variable representing the crack in a specific layer.

Furthermore, Gonenli and Das (2021) [136] developed a mathematical model to explore the impact of through-thickness damage on thin plate frames of different configurations, highlighting how much the location of damage affects the strength of the structure. Aftab et al. initiated a two-phase investigation into breathing cracks in plate-like structures in 2021, using DR analysis and Hilbert transform to assess crack severity [137]. Their follow-up study in 2022 presented a crack identification technique based on instantaneous frequency ratio (IFR), highlighting the importance of different excitation types for damage indication and severity estimation. Nikkhoo et al. (2022) [138] analyzed thin RP with cracks under moving masses and found that the mass weight and velocity, crack dimensions, angular orientations, and plate aspect ratios significantly influenced the dynamic outcomes. They noted that moving masses affected the plates' dynamics more than moving loads. Song et al. (2022) [139] established a methodology for analyzing the free vibrations of hexagonal plates, both intact and cracked, focusing on the impact of crack length and inclination on their natural frequencies and mode configurations under various boundary conditions. Al-shammari et al. (2022) [140] examined the vibrational effects of central apertures and cracks on the RP, observing a correlation between fundamental frequency and aperture diameter, with cracks reducing the frequency. Migot et al. (2023) [141] focused on fatigue crack detection using local vibration techniques, validated by scanning laser Doppler vibrometer (SLDV) and electromechanical impedance spectroscopy (EMIS). Wang et al. (2023) [142] investigated the vibration of cracked ferromagnetic plates subjected to in-plane forces and a magnetic field, focusing on the first mode of natural frequency. Finally, the damage and DR of structures subjected to impact or blast loads have been extensively discussed in numerous studies [143–146]. For example, Wang et al. (2024) [147] investigated the damage and the DR of rectangular steel plates under near-surface blast conditions. Their study combined full-scale tests and numerical simulations to analyze how factors like explosion yield, height, angle, and steel plate thickness affected structural integrity. Finally, Table 2 summarizes significant forward research investigations related to damage identification in UT plates.




Figure 2. Variation of the first 15 natural frequencies with respect to crack (a) location ratio and (b) length ratio [99].




Figure 3. Frequency response curve at different crack angles, where a_4 is the peak amplitude at mode 4, and σ_2 is the second perturbation parameter [132].

Table 1. Natural frequencies of a damaged plate under various boundary conditions [7].

Lengths of the Sides of the Plate		CCFF		CCSS		SSSS	
		1-Mode Natural Frequency, ω_{mn} (rad/s) for a ½-Crack Length, a = 0.05 (m)					
		Intact	Damaged	Intact	Damaged	Intact	Damaged
I_1 (m)	I_2 (m)						
1	1	80.46	70.56	445.67	403.78	77.58	71.12
0.5	1	231.06	227.61	1161.77	1138.53	193.95	189.58
0.5	0.5	321.85	282.24	1782.66	1615.12	310.32	284.48

Table 2. Summary of forward studies that discuss the detection of damage in UT plates.

Author	Method	Type of Damage	Plate Shape
Hu et al. 2020 [148]	Symplectic superposition method	Side crack	RP
Xue et al. 2020 [149]	RRM	Side crack	
Das et al. 2023 [150]	Back-propagated artificial neural networks (ANN)	Central crack	
Bachene et al. 2009 [151]	Extended FEM	Central crack	
Tran et al. 2015 [152]	Extended iso geometric approach (XIGA) and HSDT	Central and edge crack	
Hu et al. 2023 [153]	Symplectic superposition method (SSM)	Edge crack	
Milazzo 2022 [154]	RRM	Central and edge crack	
Li et al. 2004 [155]	Strain energy method	Surface crack	CP
Rucka et al. 2006 [156]	Wavelet-based	Central defect	SP
Dwivedi et al. 2023 [157]	Higher-order XFEM	Edge and internal crack	

3.1.2. Plate of Thickness (VT)

A few studies have focused on the oscillatory behavior of cracked plates of VT. Wang et al. (2008) [158] examined the dynamics of viscoelastic RP with VT and the impact of cracks on their vibrational properties by applying the differential quadrature methodology. The study established differential equations to describe the motion of a viscoelastic plate whose thickness varies linearly and contains part-through cracks. These equations include terms for the additional rotation caused by the cracks. The study revealed that the dimensionless complex frequencies, which describe the vibrational properties of a system, are influenced by the material's non-dimensional delay time, the plate's aspect and thickness ratio, and the characteristics of any cracks present. The research shows that cracks impact vibration by changing these frequencies, particularly when they are closer to the plate's center, which decreases the rigidity of the plate. Moreover, a higher number of cracks leads to a significant decrease in frequency, whereas an increase in the plate's aspect and thickness ratios results in a considerable increase in frequency. Gupta et al. (2018) [27] combined classical plate theory with modified couple stress theory to develop an analytical model to understand the nonlinear vibration dynamics of cracked RP with LVT and PVT. In Table 3, their research showed that the fundamental frequency rose as the taper parameter increased in both one and two directions, with a more pronounced effect in the latter. Furthermore, the fundamental frequency increased with the taper parameter more significantly in PVT than in LVT. Additionally, an increase in crack length and gradient index resulted in a reduction in the fundamental frequency. The impact of boundary conditions on the fundamental frequency was also significant. Importantly, their results revealed similar vibrational behaviors between the UT and VT plates affected by cracks, though the magnitudes of influence differed.

From 2019 to 2021, Minh et al. [159–164] conducted a series of studies on FGM plates with LVT and central cracks, investigating the effects of crack dimensions, material volume fraction exponents, and plate thickness on vibration frequencies. They used various shear deformation theories to analyze stability and vibrational parameters, considering factors like temperature, boundary conditions, and plate geometry. The study's findings indicated that several factors contributed to reduced vibration frequency in plates. An increase in crack length, length-to-width ratio, and power-law index all led to decreased plate stiffness and vibration frequency. Additionally, plates with a higher ratio of initial to final thickness (h_0/h_a) exhibited a more significant reduction in vibration frequency. In 2020, Heo et al. [165] examined the free vibration of cracked plates of LVT, employing the peridynamics (PD) approach. They found that thicker plates had higher natural frequency values, while longer cracks led to lower frequencies. Interestingly, larger crack orientation resulted in higher frequencies, and plates with LVT showed mode shapes favouring their thinner ends. Chandrakar et al. (2021 and 2022) [87,166] studied the nonlinear vibrations of cracked isotropic and orthotropic plates with LVT and PVT. They observed that the nonlinearity of the plate increased with the increasing or decreasing value of the taper

parameter. A plate with PVT was more nonlinear compared to LVT cases. Additionally, the presence of a crack further increased the nonlinearity of the plate. Le et al. (2023) [167] combined the FSDT and FE methods to study the vibrational properties of the RP with PVT and multi cracks. Their results showed that when a plate's crack length increases or the number of cracks grows, its stiffness decreases, leading to a lower free vibration frequency. Similarly, an increase in the sheet thickness ratio or the plate length ratio, which makes the plate thinner, also resulted in a reduction in the vibration frequency, as shown in Figure 4.




Figure 4. The correlation between the frequency parameter and the index of parabolic varying thickness (PVT) contains 3 cracks, where (c) crack length, (d) distance between cracks, and (a and b) plate length and width, respectively [167].

Table 3. Impact of varying thickness gradient index, crack size, and taper factor on the basic vibration frequency of a FGM plate with all edge simply supported (SSSS) boundary conditions, taking into account both one-dimensional and two-dimensional models [27].

Thickness Variation	Gradient Index 'n'	Crack Length 'a'	Fundamental Frequency ω (rad/s)				
			Taper Parameter				
			$\alpha = \beta = 0$	α (1 D)		$\alpha = \beta$ (2 D)	
				0.5	1	0.5	1
LVT	0	0	719.70	731.55	752.15	736.10	756.10
		0.01	700.11	711.98	732.60	716.54	736.56
		0.02	685.82	697.70	718.35	702.27	722.31
		0.05	674.91	671.31	692.02	675.89	696.00
	0.5	0	505.66	513.98	528.45	517.18	531.23
		0.01	491.90	500.23	514.72	503.44	517.50
		0.02	481.85	490.20	504.71	493.41	507.49
		0.05	463.27	471.66	486.21	474.88	489.00
PVT	0	0	719.70	736.19	769.07	746.37	786.59
		0.01	700.11	716.94	750.04	727.37	767.90
		0.02	685.82	703.04	736.45	713.78	754.72
		0.05	659.37	677.70	711.94	689.26	731.32
	0.5	0	505.66	517.25	540.34	524.40	552.66
		0.01	491.90	503.72	526.98	511.05	539.52
		0.02	481.85	493.96	517.42	501.50	530.26
		0.05	463.27	476.15	500.21	484.27	513.83

3.2. Inverse Problem for the DR of the Cracked Plate

Employing the DR measurements to identify the crack location and size is known as an inverse problem. The primary theory of vibration-based damage detection is based on

the dependency of modal parameters on the physical properties of the structure under inspection. Damage-caused changes in the structure's physical properties lead to clear changes in modal parameters (including natural frequencies, modal damping, and mode shapes). Research effectively substantiates the application of DR measurements for damage detection in plate structures; however, compared with the forward problem, there is much less research on the inverse problem.

The study of this type of inverse problem began in 1978, when Adams et al. [168] introduced a methodology to identify damage in a one-dimensional structure by analyzing the changes in its longitudinal vibration frequencies. Lee et al. (1997, 2001, 2003) [169–171] developed a series of crack models and damage detection techniques for plate structures. Their initial crack model, introduced in 1997, used the strain energy equivalence principle (SEEP) to detect damage in elliptical through-cracks in 2D and 3D elastic solids [169]. In 2001, they developed a novel structural damage identification method for plate structures, utilizing frequency response functions (FRFs) as its foundation. This method, rooted in the principles of the dynamic equation of motion, employed a damage distribution function to effectively characterize the extent and location of damage within the structure [170]. In 2003, they developed a new damage identification theory for thin plates with line micro-cracks using the effective stiffness model and the FRF. However, this theory, limited to micro-cracked plates not close to boundaries, requires experimental validation, as it has only been demonstrated numerically [171]. Cornwell et al. (1999) [172] explored the effectiveness of strain energy-based methods for damage detection in plate-like structures through a comprehensive research program encompassing both experimental and numerical studies. These methods efficiently localized areas of reduced stiffness down to 10% accuracy with the use of limited modes. This technique only needed the comparison of the structure's mode shapes pre- and post-damage. Li et al. (2002) [173] implemented the strain mode technique through numerical simulations and experiments to pinpoint damage locations in plate-like structures, utilizing an aluminum plate with free boundary conditions as their test subject. Their findings, detailed in Figure 5, revealed a consistent correlation between the simulation and experimental results. This was particularly evident in identifying areas of damage based on the bending moment index $\bar{\beta}_{r,x}$. This index proved to be a reliable indicator for locating damage, as evidenced by the congruence of the major maximum of residual strain $\Delta\bar{\epsilon}_{r,x}$ at the damaged area and minor maxima near it.

After that, Wu and Law (2004–2005) [174–179] made significant contributions to the field of damage identification in plate structures and developed various methods for locating and quantifying damage using vibration measurements. The authors conducted a comprehensive comparison of various damage localization techniques. Their findings revealed that uniform load surface (ULS) curvature surpassed other methods in terms of damage localization sensitivity, particularly under conditions of incomplete and noisy measurements, as demonstrated in Figure 6 [174]. Additionally, they proposed an anisotropic damage model to detect edge-parallel cracks in thin RP and compared their results with Lee's 1997 [169] model [175]. Additionally, the researchers proposed a novel damage localization technique for two-dimensional plate structures, employing changes in ULS curvature as the primary indicator [176]. Additionally, they developed a new method for damage localization in two-dimensional plate structures based on changes in the ULS curvature [177]. Subsequently, they improved their previous study to identify the specific location and measure the severity of damage in two-dimensional plate structures using a sensitivity-based method with ULS curvature, effectively showing the damage location and magnitude, as seen in Figure 7 [178]. Their work was further extended by proposing a new anisotropic damage model for detecting cracks in plates with edge-parallel cracks [179]. Their work has been experimentally and numerically validated, and their methods have demonstrated their ability to identify a variety of damage types including cracks, delamination, and stiffness reductions.

In 2004, Yam et al. [180] developed a strategy for detecting damage in structures using vibration analysis on a honeycomb sandwich plate and identified future research

areas despite experimental errors. Subsequently, in 2005, Yam et al. examined damage in composite plates with internal cracks and delamination, using piezoelectric devices for measurements. This study found a relationship between damage characteristics and changes in modal parameters, with delamination locations identifiable through damping and strain energy changes [181]. The technique by Huynh et al. (2004) [182] used non-destructive vibration tests for damage identification in plate structures. By employing the FEM data of an intact structure and its FRF, they formulated a damage location vector (DLV). This DLV method effectively located and assessed the damage, even with noisy and incomplete data. Furthermore, in 2005 [183], the authors proposed another method for early-stage damage detection where there was no substantial change in mass or damping. The method related alterations in FRFs to shifts in the structural stiffness matrix, with the DLV evaluation showcasing this relationship. An experiment was conducted where element 11 was altered to mimic internal damage. Analysis of the FRF data via the DLV identified element 11 and its neighboring nodes as damaged, with the impact on neighboring nodes being significantly lesser and decreasing with distance from element 11, as shown in Figure 8.

Moreover, Qiao and Lestari (2008) [184] developed a novel method that combined static/dynamic approaches to improve damage detection in composite plates. This technique, identifying changes in the DR due to damage, used two actuator-sensor systems to measure the DR and utilized both experimental and numerical mode shapes to detect delamination. The researchers successfully identified, located, and quantified the extent of delamination and the effect of static load on the DR. The researchers concluded that this method effectively enhanced damage detection by amplifying the damage's impact. Ramos et al. (2010) [185] explored dynamic-based methods for damage identification in arched structures using ambient and random impact vibrations. They applied stochastic subspace identification (SSI), the mode shape curvature method (MSCM), and FEM updating to detect and assess structural damage. The study found that while some methods successfully identified damage, others struggled due to noise and sensitivity to geometric changes. They concluded that a combination of methods provided the most reliable results, emphasizing the need for robust techniques in early damage detection for historical structures. Trana (2010) [186] introduced a new technique for detecting cracks in different structures including metallic and reinforced concrete under real-world conditions. The study compared the DLV and Maia FRF curvature difference (MFCD) methods. While MFCD, working solely with FRF, was specialized for beams, the DLV offered a more comprehensive application but required a dynamic stiffness matrix. Xu et al. (2013) [187] presented a technique for detecting plate damage using two-dimensional Gaussian wavelets, laser-scanned deflection shapes, and focused on harmonic excitation-induced vibrations, with data collected via a scanning laser vibrometer.

Furthermore, Fu et al. (2013) [188] introduced a novel damage detection technique for plate structures using dynamic response sensitivity-based finite element model updating (DRSBFEMU). While this method effectively identified local damage in plates from a small number of acceleration measurements, it became computationally expensive and less accurate in scenarios with large finite element discretization. To address this limitation, Fu et al. (2016) [189] proposed a two-stage damage identification method. The first stage utilizes the modal strain energy change ratio (MSECR) to identify potential damage locations, along with a method to minimize false alarms caused by the "vicinity effect". These identified elements are then considered suspicious for further investigation. In the second stage, the DRSBFEMU method quantifies the extent of damage for these suspicious elements, reducing the number of unknowns and significantly decreasing the computational time. The effectiveness and efficiency of the proposed method were demonstrated using a cantilevered plate and a two-span continuous plate. The results confirm the method's ability to identify damage in plates from a few acceleration measurements. However, as shown in Figure 9, noise interference can lead to false alarms in the damaged locations identified using the improved MSECR method.

Recently, Al-agamy et al. (2019) [190] explored damage detection in composite plates through a theoretical and experimental study using the DLV method. The FEM was employed for theoretical simulation of a damaged plate, followed by a shaker test on a centrally damaged plate under two different boundary conditions. The DLV method successfully identified intentionally damaged elements in the plate, with primary data peaks pinpointing the damage and secondary peaks showing affected neighboring nodes, though the impact on these was less significant. The study concluded that the DLV method could effectively locate damage. Huang et al. (2019) [191] investigated the geometric features of phase diagrams for cantilever beams with breathing cracks and proposed a novel method for crack identification based on these features. The study emphasized how the presence of a crack influenced the dynamics of the system, particularly under primary and super-harmonic resonance conditions. The authors introduced multiple identification indices, such as quasi-standard deviation and vertical segmentation methods, which are used to analyze changes in the phase diagram's area due to variations in crack depth and location. Their findings suggest that phase diagrams, especially under super-harmonic resonance, are highly sensitive to crack parameters, making the proposed method both feasible and effective to accurately determine crack characteristics in engineering structures. Duvnjak et al. (2021) [192] successfully employed the mode shape damage index (MSDI) to detect discrete damage in plate-like structures. Experimental validation demonstrated the MSDI method's capability to identify the presence of damage, pinpoint single or multiple damage locations, and assess damage severity in cases of single discrete damage. Finally, Table 4 summarizes significant research investigations related to damage identification in UT plates.




Figure 5. The bending moment index ($\bar{\beta}_{r,x}$) results for (a) modes (1,1) and (b) mode (2,1), along with the residual strain mode shape index ($\Delta \bar{\epsilon}_{r,x}$) results for (c) modes (1,1) and (d) mode (2,1) [173].




Figure 6. Comparison between different methods for locating damage based on changes in the modal flexibility: (a) index of flexibility change; (b) index of uniform load surface (ULS) change; (c) index of flexibility curvature; (d) index of ULS curvature [174].




Figure 7. Damage magnitude percentage for the two-dimensional cracked plate [178].




Figure 8. Damage detection in element 11 by the damage location vector method [183].




Figure 9. Enhanced modal strain energy change ratio (MSECR) method localization of multiple defects in a two-span plate with 2% noise [189].

Table 4. Summary of damage identification research in plates of uniform thickness (UT).

Author	Method	Type of Damage	Material	Plate Shape
Wei et al. 2005 [193]	Nonlinear autoregressive moving average with exogenous excitation (ARMAX)	Delamination	Composite	RP
Zhang et al. 2012 [194]	Mode shape curvature (MSC)	Single impact damages	Plywood	
Wei et al. 2016 [195]	MSECR	Single and multi-damage	Isotropic	
Castro et al. 2018 [196]	Electro-mechanical impedance (EMI) and FRF	Central crack	Aluminum	
Yam et al. 2002 [197]	MSC and strain FRF	2-Out-of-plane deflection	Steel	
Zhang et al. 2013 [198]	Operating deflection shape curvature (ODSC)	Delamination	Plywood	Squire Plate (SP)
Alsaadi et al. 2020 [199]	FRF	Delamination	Glass fiber composite laminate	
Zhong et al. 2014 [200]	2D-Multiple signal classification (MUSIC)	2-Delamination	Carbon fiber composite	
He and Yuan, 2016 [201]	SPT	3-damage location	T6061 aluminum	
Katunin, 2011 [202]	Two-dimensional B-spline wavelets	Crack, notch and spatial damage	polymeric composite	
Cao et al. 2013 [203]	FD	Small cross-shaped crack	Aluminum	
Huang et al. 2021 [204]	NODIS-based	Delamination	Isotropic plate	
Zuo et al. 2018 [205]	2D-MUSIC	2-damage location	Laminate composite	
Reddy et al. 2012 [206]	FRF	4-Different damage cases	Aluminum	

4. Discussion

This section offers an in-depth analysis of plate theories, with a focus on modeling cracks and thickness variation in governing equations of plates and exploring damage detection methods in plate structure. The discussion aims to methodically evaluate the benefits, constraints, and complexities inherent in these areas.

Plate theories provide a fundamental framework for understanding the behavior of thin plates under various loading conditions and boundary constraints. These theories are essential for designing safe and efficient plate structures in a wide range of engineering applications. However, these theories have both advantages and disadvantages that need to be carefully considered when selecting the most appropriate theory for a specific application. Classical plate theories, such as the Euler–Bernoulli, Lagrange, Navier, and Kirchhoff theories, provide valuable tools for analyzing thin plates under static loading, but they have limitations. These theories cannot accurately predict the behavior of thick plates, plates with large deflections, or plates made of nonlinear or anisotropic materials. Additionally, they are not suitable for analyzing plates subjected to shear loads, dynamic loads, or three-dimensional effects. Additionally, the Rayleigh plate theory further restricts its applicability to thin plates with small deflections and linear elastic, homogeneous, and isotropic materials. To address these limitations, more sophisticated plate theories have been developed. The MR plate theory relaxes the assumption of negligible shear strains, allowing for the modeling of transverse shear deformation and stresses. This theory provides more accurate predictions for thick plates or plates with high aspect ratios. However, its ability to handle nonlinear materials or dynamic loads is still limited. For even more complex behaviors, such as three-dimensional effects and nonlinear material properties, HSDT incorporates additional terms in the governing equations. These theories provide the most accurate predictions but are computationally more demanding and may not be necessary for all applications. Generally, the selection of plate theory depends on the specific characteristics of the plate, the loading conditions, and the required level of accuracy. Classical plate theories are suitable for simple plate geometries and moderate loading conditions. For more complex problems or situations where high accuracy is required, more advanced plate theories, such as the MR or HSDT, should be used.

The governing equations differ for damaged and undamaged plates in accounting for the presence of damage. In an undamaged plate, the material properties are assumed to be uniform throughout the plate. This means that the governing equations can be expressed in a relatively simple form. However, in a damaged plate, the material properties are no longer uniform. This is because the damage has caused a change in the stiffness, mass, and damping properties of the plate. As a result, the governing equations for a damaged plate must be more complex in order to account for these changes. Modeling the behavior of damaged plates requires modifying the governing equations to account for the changes in material properties caused by the damage. Two main approaches exist, explicit damage modeling, which directly incorporates the damage characteristics into the equations [207–211], and implicit damage modeling, which utilizes a damage parameter to represent the overall impact on the plate's behavior [212–215]. The selection of the approach depends on the damage complexity and desired accuracy. Explicit modeling is suitable for simple damage types, while implicit modeling is more appropriate for complex damage scenarios. Generally, governing equations for damaged plates are more intricate and computationally demanding due to the introduction of additional unknowns, necessitating the use of numerical methods for solutions. Moreover, the governing equations for plates of UT are relatively simple and can be derived using classical plate theories, while those for plates of VT are more complex and require additional considerations. This is primarily due to the presence of thickness variation in VT plates, which leads to more intricate behavior and necessitates the incorporation of a thickness function into the governing equations. The analysis of VT plates is consequently more challenging than that of UT plates.

The forward problem shows that an increase in crack length, size, depth, and angle typically leads to a decrease in the natural frequencies, a common observation in vibration

characteristics. The growth or reorientation of a crack reduces the plate's overall stiffness, which in turn lowers the natural frequencies, causing the plate to vibrate at slower speeds for the same mode shapes. Moreover, the presence of cracks can alter the modal shapes, introducing localized flexibility and leading to more significant vibrations in certain areas, resulting in distortions or asymmetries compared to an uncracked plate. The location of a crack also significantly affects the vibration characteristics. Internal cracks, for example, have a more pronounced impact on natural frequencies than surface cracks. Because the internal cracks cut deeper into the plate, effectively removing material and reducing its overall stiffness, this drop in stiffness significantly lowers the natural frequencies, as the plate vibrates slower with less rigidity. Additionally, the shape of the plate influences its frequencies, which is a complex interplay of various factors. For instance, the CP under SSSS and CCCC boundary conditions with UT generally exhibited the lowest frequency compared to other shapes [216]. Plates with higher aspect ratios also tend to have higher fundamental frequencies due to their reduced bending capacity. The boundary conditions and material properties of the cracked plate are crucial in determining the vibrational characteristics, with different boundary conditions and materials significantly affecting the natural frequencies. Finally, the type of excitation condition can significantly influence the frequency response of a vibrating system. The nature of vibration affects the plate's frequency response by determining which natural frequencies are excited and to what extent based on the frequency content, duration, and damping of the excitation.

In the field of inverse damage detection, numerous DR techniques have been utilized. Each of these techniques comes with its own set of advantages and disadvantages. For instance, vibration-based monitoring is a promising technique for structural damage detection due to its ability to identify damage by analyzing changes in the dynamic properties of a structure [217]. These dynamic properties, such as natural frequencies, mode shapes, and damping ratios, are sensitive to changes in stiffness caused by structural damage. Various methods have been developed to detect damage based on these properties including methods based on changes in natural frequencies [218], mode shapes [219,220], and their derivatives [221–226]. Additionally, non-modal methods, such as the FRF method [227] and guided waves approach [228], can also be used for damage detection but often require additional algorithms to enhance their effectiveness. Furthermore, the DRSBFEMU method has shown promise in real-world applications [188]. This was compared to methods used in [229–231] and found to be more accurate in identifying simulated damage in a plate. The DRSBFEMU method was particularly close to the true values in its identification results and is a promising tool for practical damage identification applications. However, it is important to note that none of these methods can predict the exact crack size.

The DLV method is a valuable tool for the SHM and has been widely used in various research projects [190,232–234]. It can successfully detect damage using only a limited number of sensors and truncated modes [235]. However, the method has some limitations [235–237]. First, it is sensitive to noise in the measured data. This is because the method relies on the difference in flexibility between a damaged structure and an undamaged structure. If the measured data are noisy, the difference in flexibility may be difficult to distinguish, as shown in Bernal's research, where the DLV error was around 1.5%, as shown in Figure 10 [237]. Second, the scalar proves to be inconsequential for localization purposes and is only of secondary importance in quantification, as reductions in stiffness can be calculated in percentages without reference to specific values. Moreover, the method is not always able to accurately identify the location and extent of damage. This is because it is based on the assumption that damaged elements are completely stiff. In reality, damaged elements may still have some stiffness, making it difficult to identify them using the DLV method. Finally, the method can be computationally expensive. This is because it requires the calculation of the flexibility matrix of the structure. The flexibility matrix is a large matrix, and its calculation can be time-consuming.

The phase diagram-based method offers several advantages including its high sensitivity to nonlinear dynamic behaviors, which are often more indicative of cracks than linear

parameters [238–241]. This method allows for the detailed analysis of crack characteristics such as location and depth, by using various indices like quasi-standard deviation and vertical segmentation to provide quantitative insights. It is effective under both primary and super-harmonic resonance conditions, with the latter being particularly sensitive to crack parameters [191]. Additionally, the method holds the potential for real-time monitoring, enabling continuous crack detection without interrupting the operation of the structure. However, the method has limitations including the complexity of nonlinear dynamics, which can be challenging to implement and interpret, and its sensitivity to noise and measurement errors, which may affect accuracy [242,243]. The method also relies on achieving specific resonance conditions, which can be difficult in practical applications, and it is currently more suited to simpler structures like cantilever beams. Furthermore, it depends on accurate knowledge of the system's dynamic parameters and crack characteristics, which might not always be readily available [244–246].

Artificial neural networks (ANN) are a powerful tool in structural health monitoring, particularly for detecting cracks and other forms of damage in composite structures, due to their ability to model complex nonlinear relationships between input data such as vibration signals, and output predictions including the presence, location, and severity of cracks [247–249]. One of the significant advantages of ANN is its capacity to handle the nonlinear relationships inherent in the data, which is particularly relevant in complex materials like composites where crack severity often exhibits nonlinear patterns [250,251]. Moreover, ANN models are robust against noise, making them effective even with noisy input data, a common scenario in real-world applications [251]. Once trained on a sufficiently diverse dataset, ANN can generalize well, enabling it to detect cracks in previously unseen structures, thus offering versatility across various applications [251]. However, challenges remain such as the need for large datasets to train the models effectively, which can be costly and time-consuming to acquire, and the difficulty in understanding the internal decision-making process of ANNs, which poses challenges in critical applications where transparency and interpretability are crucial [250].

Detecting damage in plates with VT using their DR presents several challenges. The DR of a plate with VT is more complex than that of a UT because the propagation of waves, such as stress waves or vibration waves, is influenced by the changing thickness, leading to variations in wave speed, attenuation, and mode conversion. These complexities make it challenging to interpret the DR signals and accurately identify the location and severity of damage. Additionally, the DR of a plate including its natural frequencies and mode shapes is significantly affected by thickness variations. This can lead to ambiguities in interpreting the DR, making it difficult to distinguish between damage-induced changes and inherent variations due to thickness variations. Moreover, the material properties of the plate of VT, such as its density, stiffness, and damping, along with its geometric features, such as curvature, holes, and other irregularities, can further complicate the DR and make damage detection more challenging. Furthermore, in some cases, damage in plates can lead to nonlinear behavior in the DR, making it difficult to model and analyze the system using conventional linear methods. In addition, environmental factors, such as temperature fluctuations and external noise, can also influence the DR of the plate, adding additional challenges to damage detection. Similarly, the DR signals obtained from damaged plates may be contaminated by noise from various sources such as background vibrations or measurement errors. Effective noise reduction techniques are crucial for accurate damage detection. Finally, analyzing the DR of plates with varying thicknesses can be computationally demanding, especially for complex geometries or high-frequency excitations. This can limit the real-time applicability of damage detection methods based on the DR. Despite these challenges, DR-based damage detection methods have been actively researched and developed, and they continue to show promise in various applications. However, research must aim to improve the accuracy, robustness, and applicability of these methods by addressing the challenges above-mentioned.




Figure 10. Damage location vector (DLV) method error [237].

5. Conclusions

In conclusion, this comprehensive review has focused on research efforts related to the fundamentals of vibration and damage detection in plate structures using DR analysis, especially for the challenge of crack location and path identification. It has been established that damage can indeed be detected through vibration tests because the existence of cracks in structural elements results in the introduction of local flexibility, which modifies the vibration responses of the members. However, several research gaps and promising directions for future investigation have been identified:

- Most research on damage detection in plates has focused on the forward problem, which is to study how crack damage affects the DR of plates. This work has provided valuable insights and developed various models for different structures. However, there is a need to apply these models to the inverse problem, which is to detect damage from vibration measurements.
- Additionally, most research on the inverse problem has focused on plates with the UT, even though plates with VT are important in many applications. This oversight needs to be addressed to comprehensively address the challenges of damage detection in the VT plates.
- Moreover, many studies on the inverse problem have not been able to accurately identify crack parameters such as size, length, and propagation rate. They often only pinpoint the damage location in plates with UT based on changes in vibration responses. Future research should focus on improving the accuracy of these parameters.
- Finally, crack path identification, a critical area of research for beam structures, has yet to be studied in plate structures. This important gap in the literature needs to be addressed.

In summary, there is a need for more research on damage detection in VT plates and crack path identification. This research is important to improve the efficiency and cost-effectiveness of structural inspections in engineering applications.

Author Contributions: Conceptualization, Y.L.A.A., F.H. and M.K.; Methodology, Y.L.A.A., F.H. and M.K.; Formal analysis, Y.L.A.A.; Investigation, Y.L.A.A.; Resources, Y.L.A.A.; Data curation, Y.L.A.A.; Writing—original draft preparation, Y.L.A.A.; Writing—review and editing, Y.L.A.A., F.H., A.A.A., and M.K.; Visualization, Y.L.A.A.; Supervision, M.K. and F.H.; Project administration, Y.L.A.A.; Funding acquisition, M.K. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Acknowledgments: The authors extend their appreciation to the Deanship of Scientific Research at Northern Border University, Arar, Saudi Arabia.

Conflicts of Interest: The authors declare no conflicts of interest.

Abbreviations

A and B	A and B are constants
SSSS	All edges simply supported
∇^4	Biharmonic operator
CP	Circular plates
CS	clamped supported
α_{tb}°	Coefficients at the center of crack
α_{bt}°	Compliance of stretching-bending
DLV	Damage location vector
ρ	Density
q	Distributed transverse loading
DR	Dynamic response
$B(x,y)$	Effective torsional rigidity
FE	Finite element
D	Flexural rigidity
DRSBFEMU	Dynamic response sensitivity-based finite element model updating
FD	Fractal dimension
FRF	Frequency response function
FGM	Functionally graded material
FSDT	First-order shear deformation theory
a	Half-crack length
HSDT	higher-order shear deformation theory
n_x	In-plane or membrane force per unit length
LSM	Line spring model
LVT	Linear varying thickness
P_z	Load acting at the surface per unit area
MR	Mindlin–Reissner
E	Modulus of elasticity
$\overline{M}_y$	Moment
NDT	Non-destructive testing
α_{bb}°	Nondimensional bending compliance
PVT	Parabolically varying thickness
ν	Poisson’s ratio
RP	Rectangular plates
RRM	Rayleigh–Ritz method
SPT	Signal processing technique
SS	Simply supported
SP	Squire plate
α_{tt}°	Stretching compliance
SHM	Structural health monitoring
h	Thickness
3D	Three dimensions
D_t	Torsional rigidity
w	Transverse deflection
CCFF	Two edges clamped and two free supported
CCSS	Two edges clamped and two simply supported
2D	Two dimensions
ULS	Uniform load surface
UT	Uniform thickness
VT	Varying thickness
WT	Wavelet transformation

References

1. Dai, H.H.; Song, Z. On a Consistent Finite-Strain Plate Theory Based on Three-Dimensional Energy Principle. *Proc. R. Soc. A Math. Phys. Eng. Sci.* **2014**, *470*, 20140494. [\[CrossRef\]](#)
2. Sanders Robert, E.; Marshall, G.J. Chapter 14. Aluminum in Marine Transportation. In *Aluminium-Technology, Industry, and Applications*; ASM International: Materials Park, OH, USA, 2023.
3. Sanders Robert, E.; Marshall, G.J. Chapter 13. Aluminum in Ground Transportation. In *Aluminium-Technology, Industry, and Applications*; ASM International: Materials Park, OH, USA, 2023.
4. Sanders Robert, E.; Marshall, G.J. Chapter 11. Aluminum in Aircraft and Space Applications. In *Aluminium-Technology, Industry, and Applications*; ASM International: Materials Park, OH, USA, 2023.
5. Zhang, Y.; Du, J. Dynamic Analysis of Two Parallel Rectangular Plates Coupled with Mechanical Links. *Int. J. Struct. Stab. Dyn.* **2021**, *21*, 2150157. [\[CrossRef\]](#)
6. Lu, C. 7.2.1 Damaged Plate. In *Damage and Repair of Aerospace Composite Materials*; SAE International: Warrendale, PA, USA, 2020.
7. Israr, A.; Cartmell, M.P.; Manoach, E.; Trendafilova, I.; Ostachowicz, W.; Krawczuk, M.; Zak, A. Analytical Modeling and Vibration Analysis of Partially Cracked Rectangular Plates with Different Boundary Conditions and Loading. *J. Appl. Mech. Trans. ASME* **2009**, *76*, 011005. [\[CrossRef\]](#)
8. Obenchain, M.B.; Nadella, K.S.; Cesnik, C.E.S. Hybrid Global Matrix/Local Interaction Simulation Approach for Wave Propagation Simulation in Composite Laminates. In Proceedings of the 54th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference, Boston, MA, USA, 8–11 April 2013; American Institute of Aeronautics and Astronautics (AIAA): Reston, VA, USA, 2013.
9. Goetz, J.; Tan, H.; Tovvar, A.; Renaud, J. Multi-Material Structural Topology Optimization for Blast Mitigation Using Hybrid Cellular Automata. In Proceedings of the 51st AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference, Orlando, FL, USA, 12–15 April 2010; American Institute of Aeronautics and Astronautics (AIAA): Reston, VA, USA, 2010.
10. Israr, A. *Vibration Analysis of Cracked Aluminium Plates*; University of Glasgow: Glasgow, UK, 2008.
11. Dimarogonas, A.D. Vibration of Cracked Structures: A State of the Art Review. *Eng. Fract. Mech.* **1996**, *55*, 831–857. [\[CrossRef\]](#)
12. Qiu, Z.; Wu, H.; Ye, C. Acceleration Sensors Based Modal Identification and Active Vibration Control of Flexible Smart Cantilever Plate. *Aerosp. Sci. Technol.* **2009**, *13*, 277–290. [\[CrossRef\]](#)
13. Khan, S.Z.; Khan, T.M.; Joya, Y.F.; Khan, M.A.; Ahmed, S.; Shah, A. Assessment of Material Properties of AISI 316L Stainless Steel Using Non-Destructive Testing. *Nondestruct. Test. Eval.* **2016**, *31*, 360–370. [\[CrossRef\]](#)
14. Chen, Z.; Gui, H.; Liao, X.; Du, M. Dynamic Response Analysis of a Bulk Carrier by Nonlinear Hydroelastic Method. *J. Mar. Sci. Eng.* **2021**, *9*, 877. [\[CrossRef\]](#)
15. Hairer, M.; Majda, A.J. A Simple Framework to Justify Linear Response Theory. *Nonlinearity* **2010**, *23*, 909–922. [\[CrossRef\]](#)
16. Spann, F. A Procedure for Comparing Dynamic Test Severities Based on Equipment Response Characteristics. *J. IEST* **1988**, *31*, 62–66. [\[CrossRef\]](#)
17. Ma, Y.; Chen, X.; Geng, Y.; Zhang, X. Effect of Clogging on the Permeability of Porous Asphalt Pavement. *Adv. Mater. Sci. Eng.* **2020**, *2020*, 4851291. [\[CrossRef\]](#)
18. He, X.; Fulton, R.E. Nonlinear Dynamics Analysis of a Laminated Printed Wiring Board. *J. Electron. Packag.* **2002**, *124*, 77–84. [\[CrossRef\]](#)
19. Zai, B.A.; Khan, M.; Khan, K.A.; Mansoor, A.; Shah, A.; Shahzad, M. The Role of Dynamic Response Parameters in Damage Prediction. *Proc. Inst. Mech. Eng. Part C J. Mech. Eng. Sci.* **2019**, *233*, 4620–4636. [\[CrossRef\]](#)
20. Limongelli, M.P.; Manoach, E.; Quqa, S.; Giordano, P.F.; Bhowmik, B.; Pakrashi, V.; Cigada, A. Vibration Response-Based Damage Detection. In *Structural Health Monitoring Damage Detection Systems for Aerospace*; Springer: Cham, Switzerland, 2021; pp. 133–173.
21. Fan, W.; Qiao, P. Vibration-Based Damage Identification Methods: A Review and Comparative Study. *Struct. Health Monit.* **2011**, *10*, 83–111. [\[CrossRef\]](#)
22. Avci, O.; Abdeljaber, O.; Kiranyaz, S.; Hussein, M.; Gabbouj, M.; Inman, D.J. A Review of Vibration-Based Damage Detection in Civil Structures: From Traditional Methods to Machine Learning and Deep Learning Applications. *Mech. Syst. Signal Process.* **2021**, *147*, 107077. [\[CrossRef\]](#)
23. Zai, B.A.; Khan, M.A.; Khan, S.Z.; Asif, M.; Khan, K.A.; Saquib, A.N.; Mansoor, A.; Shahzad, M.; Mujtaba, A. Prediction of Crack Depth and Fatigue Life of an Acrylonitrile Butadiene Styrene Cantilever Beam Using Dynamic Response. *J. Test. Eval.* **2020**, *48*, 20180674. [\[CrossRef\]](#)
24. Alotaibi, M.; Honarvar Shakibaei Asli, B.; Khan, M. Non-Invasive Inspections: A Review on Methods and Tools. *Sensors* **2021**, *21*, 8474. [\[CrossRef\]](#)
25. Zai, B.A.; Khan, M.A.; Khan, K.A.; Mansoor, A. A Novel Approach for Damage Quantification Using the Dynamic Response of a Metallic Beam under Thermo-Mechanical Loads. *J. Sound Vib.* **2020**, *469*, 115134. [\[CrossRef\]](#)
26. Alshammari, Y.L.A.; He, F.; Khan, M.A. Modelling and Investigation of Crack Growth for 3D-Printed Acrylonitrile Butadiene Styrene (ABS) with Various Printing Parameters and Ambient Temperatures. *Polymers* **2021**, *13*, 3737. [\[CrossRef\]](#)
27. Gupta, A.; Jain, N.K.; Salhotra, R.; Joshi, P.V. Effect of Crack Location on Vibration Analysis of Partially Cracked Isotropic and FGM Micro-Plate with Non-Uniform Thickness: An Analytical Approach. *Int. J. Mech. Sci.* **2018**, *145*, 410–429. [\[CrossRef\]](#)

28. Francese, A.; Khan, M.; He, F. Role of Dynamic Response in Inclined Transverse Crack Inspection for 3D-Printed Polymeric Beam with Metal Stiffener. *Materials* **2023**, *16*, 3095. [CrossRef]
29. Yang, Z.; He, F.; Khan, M. An Empirical Torsional Spring Model for the Inclined Crack in a 3D-Printed Acrylonitrile Butadiene Styrene (ABS) Cantilever Beam. *Polymers* **2023**, *15*, 496. [CrossRef] [PubMed]
30. Aravanis, T.-C.I.; Sakellariou, J.S.; Fassois, S.D. Damage Precise Localization under Varying Operating Conditions via the Vibration-Data-Based Functional Model Method: Formulation and Experimental Validation. *J. Sound Vib.* **2022**, *535*, 117078. [CrossRef]
31. Zhang, Y.; Bernal, D. Damage Localization from Projections of Free Vibration Signals. *J. Sound Vib.* **2017**, *394*, 146–154. [CrossRef]
32. Xu, W.; Zhu, W.; Cao, M.; Wu, H.; Zhu, R. A Novel Damage Index for Damage Detection and Localization of Plate-Type Structures Using Twist Derivatives of Laser-Measured Mode Shapes. *J. Sound Vib.* **2020**, *481*, 115448. [CrossRef]
33. Tondreau, G.; Deraemaeker, A. Automated Data-Based Damage Localization under Ambient Vibration Using Local Modal Filters and Dynamic Strain Measurements: Experimental Applications. *J. Sound Vib.* **2014**, *333*, 7364–7385. [CrossRef]
34. Haywood-Alexander, M.; Dervilis, N.; Worden, K.; Dobie, G.; Rogers, T.J. Informative Bayesian Tools for Damage Localisation by Decomposition of Lamb Wave Signals. *J. Sound Vib.* **2022**, *535*, 117063. [CrossRef]
35. Manoach, E.; Trendafilova, I. Large Amplitude Vibrations and Damage Detection of Rectangular Plates. *J. Sound Vib.* **2008**, *315*, 591–606. [CrossRef]
36. Timoshenko, S. *History of Strength of Materials: With a Brief Account of the History of Theory of Elasticity and Theory of Structures*; Dover Publications: Mineola, NY, USA, 1983; ISBN 0486611876.
37. Szilard, R. *Theories and Applications of Plate Analysis: Classical, Numerical and Engineering Methods*; John Wiley and Sons Ltd.: Hoboken, NJ, USA, 2004.
38. Rayleigh, J.W.S.B. *The Theory of Sound*; Cambridge University Press: Cambridge, UK, 1877; ISBN 9781108032209. Available online: https://books.google.co.uk/books/about/The_Theory_of_Sound.html?id=v4NSAlsTwnQC&redir_esc=y (accessed on 1 September 2024).
39. Rayleigh, J.W.S.B. *The Theory of Sound*; Dover Publications, Inc.: New York, NY, USA, 1945; Volume 2, Available online: https://books.google.co.uk/books/about/The_Theory_of_Sound.html?id=Frvgu1wSffUC&redir_esc=y (accessed on 1 September 2024).
40. Timoshenko, S.P. On the Correction for Shear of the Differential Equation for Transverse Vibrations of Prismatic Bars. *Lond. Edinb. Dublin Philos. Mag. J. Sci.* **1921**, *41*, 744–746. [CrossRef]
41. Tomotika, S. The Transverse Vibration of a Square Plate Clamped at Four Edges. *Lond. Edinb. Dublin Philos. Mag. J. Sci.* **1936**, *21*, 745–760. [CrossRef]
42. Young, D. Vibration of Rectangular Plates by the Ritz Method. *J. Appl. Mech.* **1950**, *17*, 448–453. [CrossRef]
43. Warburton, G.B. The Vibration of Rectangular Plates. *Proc. Inst. Mech. Eng.* **1954**, *168*, 371–384. [CrossRef]
44. Reissner, E. The Effect of Transverse Shear Deformation on the Bending of Elastic Plates. *J. Appl. Mech.* **1945**, *12*, A69–A77. [CrossRef]
45. Mindlin, R.D. Influence of Rotatory Inertia and Shear on Flexural Motions of Isotropic, Elastic Plates. *J. Appl. Mech.* **1951**, *18*, 31–38. [CrossRef]
46. Chen, H.; Kumar, A.V. Implicit Boundary Approach for Reissner-Mindlin Plates. In Proceedings of the Volume 2A: 33rd Computers and Information in Engineering Conference, Portland, OR, USA, 4–7 August 2013; American Society of Mechanical Engineers: New York, NY, USA, 2013.
47. Lo, K.H.; Christensen, R.M.; Wu, E.M. A High-Order Theory of Plate Deformation—Part 1: Homogeneous Plates. *J. Appl. Mech.* **1977**, *44*, 663–668. [CrossRef]
48. Lo, K.H.; Christensen, R.M.; Wu, E.M. A High-Order Theory of Plate Deformation—Part 2: Laminated Plates. *J. Appl. Mech.* **1977**, *44*, 669–676. [CrossRef]
49. Challamel Noël, K.J.T.I. 2.3.2 Reduction of the Governing Equations by Mathematical Techniques. In *Modern Trends in Structural and Solid Mechanics 2: Vibrations*; John Wiley & Sons: Hoboken, NJ, USA, 2021.
50. Reddy, J.N. A Simple Higher-Order Theory for Laminated Composite Plates. *J. Appl. Mech.* **1984**, *51*, 745–752. [CrossRef]
51. Neves, A.M.A.; Ferreira, A.J.M.; Carrera, E.; Roque, C.M.C.; Cinefra, M.; Jorge, R.M.N.; Soares, C.M.M. A Quasi-3D Sinusoidal Shear Deformation Theory for the Static and Free Vibration Analysis of Functionally Graded Plates. *Compos. B Eng.* **2012**, *43*, 711–725. [CrossRef]
52. Ghazwani, M.H.; Alnujaie, A.; Van Vinh, P.; Sedighi, H.M. Effects of Porosity and Nonlocality on the Low- and High-Frequency Vibration Characteristics of Al/Si3N4 Functionally Graded Nanoplates Using Quasi-3D Theory. *Arch. Civ. Mech. Eng.* **2024**, *24*, 49. [CrossRef]
53. Li, R.; Yang, Z.; Chen, G.; Wu, B. Analytical Solutions for Nonlinear Deflections of Corner-Fillet Leaf-Springs. *Mech. Mach. Theory* **2021**, *157*, 104182. [CrossRef]
54. Akhavan, H.; Ribeiro, P.; de Moura, M.F.S.F. Large Deflection and Stresses in Variable Stiffness Composite Laminates with Curvilinear Fibres. *Int. J. Mech. Sci.* **2013**, *73*, 14–26. [CrossRef]
55. Karagiozova, D.; Yu, T.X.; Shi, S.Y.; Zhu, L. On the Influence of Elasticity on the Large Deflections Response of Circular Plates to Uniform Quasi-Static Pressure. *Int. J. Mech. Sci.* **2017**, *131–132*, 894–907. [CrossRef]
56. Yamaki, N. Influence of Large Amplitudes on Flexural Vibrations of Elastic Plates. *ZAMM Z. Angew. Math. Mech.* **1961**, *41*, 501–510. [CrossRef]

57. Wah, T. Large Amplitude Flexural Vibration of Rectangular Plates. *Int. J. Mech. Sci.* **1963**, *5*, 425–438. [[CrossRef](#)]
58. SRINIVASAN, A.V. Large Amplitude-Free Oscillations of Beams and Plates. *AIAA J.* **1965**, *3*, 1951–1953. [[CrossRef](#)]
59. Stanišić, M.M.; Payne, J.G. A Rapidly Converging Technique for Vibration Analysis of Plates with a Discrete Mass Distribution. *Ing. Arch.* **1968**, *37*, 189–195. [[CrossRef](#)]
60. Rehfield, L.W. Nonlinear Free Vibrations of Elastic Structures. *Int. J. Solids Struct.* **1973**, *9*, 581–590. [[CrossRef](#)]
61. Mei, C. Finite Element Displacement Method for Large Amplitude Free Flexural Vibrations of Beams and Plates. *Comput. Struct.* **1973**, *3*, 163–174. [[CrossRef](#)]
62. Mazumdar, J.; Jones, R. A Simplified Approach to the Large Amplitude Vibration of Plates and Membranes. *J. Sound Vib.* **1977**, *50*, 389–397. [[CrossRef](#)]
63. Karmakar, B.M. Amplitude-Frequency Characteristics of Non-Linear Vibrations of Clamped Elliptic Plates Carrying a Concentrated Mass. *Int. J. Non-Linear Mech.* **1978**, *13*, 351–359. [[CrossRef](#)]
64. Benamar, R.; Bennouna, M.M.K.; White, R.G. The Effects of Large Vibration Amplitudes on the Fundamental Mode Shape of a Fully Clamped, Symmetrically Laminated Rectangular Plate. In Proceedings of the 4th International Conference on Recent Advances in Structural Dynamics, Southampton, UK, 15–18 July 1991; pp. 749–760. Available online: <https://ui.adsabs.harvard.edu/abs/1991sdra.proc..749B/abstract> (accessed on 1 September 2024).
65. Benamar, R.; Bennouna, M.M.K.; White, R.G. The Effects of Large Vibration Amplitudes on the Mode Shapes and Natural Frequencies of Thin Elastic Structures, Part II: Fully Clamped Rectangular Isotropic Plates. *J. Sound Vib.* **1993**, *164*, 295–316. [[CrossRef](#)]
66. Benamar, R.; Bennouna, M.M.K.; White, R.G. The Effects of Large Vibration Amplitudes on the Mode Shapes and Natural Frequencies of Thin Elastic Structures Part I: Simply Supported and Clamped-Clamped Beams. *J. Sound Vib.* **1991**, *149*, 179–195. [[CrossRef](#)]
67. Abdelali, H.M.; Bikri, K.E.; Benamar, R. *The Effects of Large Vibration Amplitudes on the Mode Shapes and Natural Frequencies of Thin Isotropic Skew Plates*; EDP Sciences: Ulis, France, 2012.
68. Lacarbonara, W. *Nonlinear Structural Mechanics*; Springer: Boston, MA, USA, 2013; ISBN 978-1-4419-1275-6.
69. Tang, D.; Zhao, M.; Dowell, E.H. Inextensible Beam and Plate Theory: Computational Analysis and Comparison with Experiment. *J. Appl. Mech.* **2014**, *81*, 061009. [[CrossRef](#)]
70. Liu, X.; Cai, G.; Peng, F.; Zhang, H.; Lv, L. Nonlinear Vibration Analysis of a Membrane Based on Large Deflection Theory. *J. Vib. Control* **2018**, *24*, 2418–2429. [[CrossRef](#)]
71. Lu, Y.; Shao, Q.; Amabili, M.; Yue, H.; Guo, H. Nonlinear Vibration Control Effects of Membrane Structures with In-Plane PVDF Actuators: A Parametric Study. *Int. J. Non-Linear Mech.* **2020**, *122*, 103466. [[CrossRef](#)]
72. Alhaifi, K.; Arshid, E.; Khorshidvand, A.R. Large Deflection Analysis of Functionally Graded Saturated Porous Rectangular Plates on Nonlinear Elastic Foundation via GDQM. *Steel Compos. Struct.* **2021**, *39*, 795.
73. Love, A.E.H. On the Small Free Vibrations and Deformations of Elastic Shells. *Philos. Trans. R. Soc. Lond.* **1888**, *179*, 491–546.
74. Von Karman, T. Festigkeitsprobleme in Maschinenbau, Encykl. *D. Math. Wiss.* **1910**, *4*, 311–385.
75. Bromberg, E.; Stoker, J.J. Non-Linear Theory of Curved Elastic Sheets. *Q. Appl. Math.* **1945**, *3*, 246–265. [[CrossRef](#)]
76. Berger, H.M. A New Approach to the Analysis of Large Deflections of Plates. *J. Appl. Mech.* **1955**, *22*, 465–472. [[CrossRef](#)]
77. Chu, H.-N.; Herrmann, G. Influence of Large Amplitudes on Free Flexural Vibrations of Rectangular Elastic Plates. *J. Appl. Mech.* **1956**, *23*, 532–540. [[CrossRef](#)]
78. Casado-Pascual, J.; Gómez-Ordóñez, J.; Morillo, M.; Hänggi, P. Two-State Theory of Nonlinear Stochastic Resonance. *Phys. Rev. Lett.* **2003**, *91*, 210601. [[CrossRef](#)] [[PubMed](#)]
79. Liu, Y.; Zhou, F.; Mao, Q. Analytical Theory for the Nonlinear Optical Response of a Kerr-Type Standing-Wave Cavity Side-Coupling to a MIM Waveguide. *Opt. Express* **2013**, *21*, 23687. [[CrossRef](#)]
80. Liu, R.; Xue, J. Development of Nonlinear Mechanics for Laminated Composite Plates and Shells. *Lixue Xuebao/Chin. J. Theor. Appl. Mech.* **2017**, *49*, 487–506. [[CrossRef](#)]
81. Yang, Z.; Xiong, W. Molecular Vibrational Polaritons towards Quantum Technologies. *Adv. Quantum Technol.* **2022**, *5*, 2100163. [[CrossRef](#)]
82. Leissa, A.W. *Vibration of Plates*; NASA: Washington, DC, USA, 1969.
83. Israr, A. Model for Vibration of Cracked Plates for Use with Damage Detection Methodologies. *J. Space Technol.* **2011**, *1*, 1.
84. Ismail, R.; Cartmell, M.P. An Investigation into the Vibration Analysis of a Plate with a Surface Crack of Variable Angular Orientation. *J. Sound Vib.* **2012**, *331*, 2929–2948. [[CrossRef](#)]
85. Rice, J.R.; Levy, N. The Part-through Surface Crack in an Elastic Plate. *J. Appl. Mech. Trans. ASME* **1972**, *39*, 185–194. [[CrossRef](#)]
86. Joseph, P.F.; Erdogan, F. Surface Crack in a Plate under Antisymmetric Loading Conditions. *Int. J. Solids Struct.* **1991**, *27*, 725–750. [[CrossRef](#)]
87. Chandrakar, B.K.; Jain, N.K.; Gupta, A. Non-Linear Vibration Analysis of Specially Orthotropic Tapered Micro-Plates with Arbitrary Located Crack: A Non-Classical Analytical Approach. *Proc. Inst. Mech. Eng. Part C J. Mech. Eng. Sci.* **2022**, *236*, 1406–1429. [[CrossRef](#)]
88. Tao, N.; Ma, Y.; Jiang, H.; Dai, M.; Yang, F. Investigation on Non-Linear Vibration Response of Cantilevered Thin Plates with Crack Using Electronic Speckle Pattern Interferometry. *Proceedings* **2018**, *2*, 539. [[CrossRef](#)]

89. Lynn, P.P.; Kumbasar, N. Free Vibration of Thin Rectangular Plates Having Narrow Cracks with Simply Supported Edges. In Proceedings of the 10th Midwestern Mechanics Conference, Fort Collins, CO, USA, 21–23 August 1967; pp. 911–928.
90. Stahq, B.; Keer, L.M. Vibration and Stability of Cracked Rectangular Plates. *Int. J. Solids Struct.* **1972**, *8*, 69–91.
91. Joseph, P.F.; Erdogan, F. A Surface Crack in Shells under Mixed-Mode Loading Conditions. *J. Appl. Mech.* **1988**, *55*, 795–804. [[CrossRef](#)]
92. Mauyama, K.; Ichnomiya, O. Experimental Study of Free Vibration of Clamped Rectangular Plates with Straight Narrow Slits. *JSME Int. J.* **1989**, *32*, 187–193.
93. Liew, K.M.; Hung, K.C.; Lim, M.K. A Solution Method for Analysis of Cracked Plates under Vibration. *Eng. Fract. Mech.* **1994**, *48*, 393–404. [[CrossRef](#)]
94. Khadem, S.E.; Rezaee, M. Introduction of Modified Comparison Functions for Vibration Analysis of a Rectangular Cracked Plate. *J. Sound Vib.* **2000**, *236*, 245–258. [[CrossRef](#)]
95. Pai, P.F.; Oh, Y.; Kim, B.-S. Detection and Estimation of Defects in a Circular Plate Using Operational Deflection Shapes. *Proc. SPIE* **2002**, *4702*, 376–388.
96. Wu, G.Y.; Shih, Y.S. Dynamic Instability of Rectangular Plate with an Edge Crack. *Comput. Struct.* **2005**, *84*, 1–10. [[CrossRef](#)]
97. Salehi-Khojin, A.; Zhamu, A.; Zhong, W.H.; Gan, Y. Effects of Patch Layer and Loading Frequency on Fatigue Fracture Behavior of Aluminum Plate Repaired with a Boron/Epoxy Composite Patch. *J. Adhes. Sci. Technol.* **2006**, *20*, 107–123. [[CrossRef](#)]
98. Israr, A.; Cartmell, M.P.; Krawczuk, M.; Ostachowicz, W.M.; Manoach, E.; Trendafilova, I.; Shishkina, E.V.; Palacz, M. On Approximate Analytical Solutions for Vibrations in Cracked Plates. *Appl. Mech. Mater.* **2006**, *5–6*, 315–322. [[CrossRef](#)]
99. Saito, A.; Castanier, M.P.; Pierre, C. Vibration Response of Cracked Cantilevered Plates near Natural Frequency Veerings. In Proceedings of the 49th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference, Schaumburg, IL, USA, 7–10 April 2008.
100. Natarajan, S.; Baiz, P.M.; Ganapathi, M.; Kerfriden, P.; Bordas, S. Linear Free Flexural Vibration of Cracked Functionally Graded Plates in Thermal Environment. *Comput. Struct.* **2011**, *89*, 1535–1546. [[CrossRef](#)]
101. Huang, C.S.; Leissa, A.W.; Chan, C.W. Vibrations of Rectangular Plates with Internal Cracks or Slits. *Int. J. Mech. Sci.* **2011**, *53*, 436–445. [[CrossRef](#)]
102. Huang, T.; Lu, H.; McFarland, D.M.; Li, W.L.; Tan, C.A.; Bergman, L.A.; Gong, J. Natural Frequency Veering and Mode Localization Caused by Straight through-Cracks in Rectangular Plates with Elastic Boundary Conditions. *Acta Mech.* **2018**, *229*, 4017–4031. [[CrossRef](#)]
103. Bose, T.; Mohanty, A.R. Vibration Analysis of a Rectangular Thin Isotropic Plate with a Part-through Surface Crack of Arbitrary Orientation and Position. *J. Sound Vib.* **2013**, *332*, 7123–7141. [[CrossRef](#)]
104. Bose, T.; Mohanty, A.R. Detection and Monitoring of Side Crack in a Rectangular Plate Using Mobility. *JVC/J. Vib. Control* **2016**, *22*, 585–594. [[CrossRef](#)]
105. Jung, W.Y.; Park, W.T.; Han, S.C. Bending and Vibration Analysis of S-FGM Microplates Embedded in Pasternak Elastic Medium Using the Modified Couple Stress Theory. *Int. J. Mech. Sci.* **2014**, *87*, 150–162. [[CrossRef](#)]
106. Khalili, S.M.R.; Shariyat, M.; Mokhtari, M. Static Tensile and Transient Dynamic Response of Cracked Aluminum Plate Repaired with Composite Patch—Numerical Study. *Appl. Compos. Mater.* **2014**, *21*, 441–455. [[CrossRef](#)]
107. Beigi, A.; Edalat, P.; Khedmati, M.R.; Fadavi, M. A Numerical Investigation into the Crack Effects on the Natural Frequencies of Plates. *Int. J. Marit. Technol.* **2014**, *2*, 29–41.
108. Joshi, P.V.; Jain, N.K.; Ramtekkar, G.D. Analytical Modeling and Vibration Analysis of Internally Cracked Rectangular Plates. *J. Sound Vib.* **2014**, *333*, 5851–5864. [[CrossRef](#)]
109. Joshi, P.V.; Jain, N.K.; Ramtekkar, G.D. Analytical Modeling for Vibration Analysis of Thin Rectangular Orthotropic/Functionally Graded Plates with an Internal Crack. *J. Sound Vib.* **2015**, *344*, 377–398. [[CrossRef](#)]
110. Joshi, P.V.; Jain, N.K.; Ramtekkar, G.D. Analytical Modelling for Vibration Analysis of Partially Cracked Orthotropic Rectangular Plates. *Eur. J. Mech. A/Solids* **2015**, *50*, 100–111. [[CrossRef](#)]
111. Joshi, P.V.; Jain, N.K.; Ramtekkar, G.D. Effect of Thermal Environment on Free Vibration of Cracked Rectangular Plate: An Analytical Approach. *Thin-Walled Struct.* **2015**, *91*, 38–49. [[CrossRef](#)]
112. Joshi, P.V.; Jain, N.K.; Ramtekkar, G.D.; Singh Viridi, G. Vibration and Buckling Analysis of Partially Cracked Thin Orthotropic Rectangular Plates in Thermal Environment. *Thin-Walled Struct.* **2016**, *109*, 143–158. [[CrossRef](#)]
113. Joshi, P.V.; Gupta, A.; Jain, N.K.; Salhotra, R.; Rawani, A.M.; Ramtekkar, G.D. Effect of Thermal Environment on Free Vibration and Buckling of Partially Cracked Isotropic and FGM Micro Plates Based on a Non Classical Kirchhoff's Plate Theory: An Analytical Approach. *Int. J. Mech. Sci.* **2017**, *131–132*, 155–170. [[CrossRef](#)]
114. Akgöz, B.; Civalek, Ö. A Microstructure-Dependent Sinusoidal Plate Model Based on the Strain Gradient Elasticity Theory. *Acta Mech.* **2015**, *226*, 2277–2294. [[CrossRef](#)]
115. Gupta, A.; Jain, N.K.; Salhotra, R.; Joshi, P.V. Effect of Microstructure on Vibration Characteristics of Partially Cracked Rectangular Plates Based on a Modified Couple Stress Theory. *Int. J. Mech. Sci.* **2015**, *100*, 269–282. [[CrossRef](#)]
116. Gupta, A.; Jain, N.K.; Salhotra, R.; Rawani, A.M.; Joshi, P.V. Effect of Fibre Orientation on Non-Linear Vibration of Partially Cracked Thin Rectangular Orthotropic Micro Plate: An Analytical Approach. *Int. J. Mech. Sci.* **2016**, *105*, 378–397. [[CrossRef](#)]
117. Gao, K.; Gao, W.; Wu, D.; Song, C. Nonlinear Dynamic Characteristics and Stability of Composite Orthotropic Plate on Elastic Foundation under Thermal Environment. *Compos. Struct.* **2017**, *168*, 619–632. [[CrossRef](#)]

118. Ghadiri, M.; Mahinzare, M.; Shafiei, N.; Ghorbani, K. On Size-Dependent Thermal Buckling and Free Vibration of Circular FG Microplates in Thermal Environments. *Microsyst. Technol.* **2017**, *23*, 4989–5001. [\[CrossRef\]](#)
119. Shojaeefard, M.H.; Saeidi Googarchin, H.; Ghadiri, M.; Mahinzare, M. Micro Temperature-Dependent FG Porous Plate: Free Vibration and Thermal Buckling Analysis Using Modified Couple Stress Theory with CPT and FSDT. *Appl. Math. Model.* **2017**, *50*, 633–655. [\[CrossRef\]](#)
120. Shojaeefard, M.H.; Saeidi Googarchin, H.; Mahinzare, M.; Eftekhari, S.A. Magnetic Field Effect on Free Vibration of Smart Rotary Functionally Graded Nano/Microplates: A Comparative Study on Modified Couple Stress Theory and Nonlocal Elasticity Theory. *J. Intell. Mater. Syst. Struct.* **2018**, *29*, 2492–2507. [\[CrossRef\]](#)
121. Mahinzare, M.; Ranjbarpur, H.; Ghadiri, M. Free Vibration Analysis of a Rotary Smart Two Directional Functionally Graded Piezoelectric Material in Axial Symmetry Circular Nanoplate. *Mech. Syst. Signal Process.* **2018**, *100*, 188–207. [\[CrossRef\]](#)
122. Mahinzare, M.; Barooti, M.M.; Ghadiri, M. Vibrational Investigation of the Spinning Bi-Dimensional Functionally Graded (2-FGM) Micro Plate Subjected to Thermal Load in Thermal Environment. *Microsyst. Technol.* **2018**, *24*, 1695–1711. [\[CrossRef\]](#)
123. Chouiyakh, H.; Azrar, L.; Alnefaie, K.; Akourri, O. Crack Identification Based on the Nonlinear Response of Plates with Variably Oriented Surface Crack. *MATEC Web Conf.* **2018**, *149*, 02061. [\[CrossRef\]](#)
124. Moradi, S.; Makvandi, H.; Poorveis, D.; Shirazi, K.H. Free Vibration Analysis of Cracked Postbuckled Plate. *Appl. Math. Model.* **2019**, *66*, 611–627. [\[CrossRef\]](#)
125. Gupta, A.; Jain, N.K.; Salhotra, R.; Joshi, P.V.; Soni, S. Effect of Crack Location on Vibration Analysis of Cracked FGM Plate under Thermal Environment. *Mater. Today Proc.* **2018**, *5*, 28043–28050. [\[CrossRef\]](#)
126. Soni, S.; Jain, N.K.; Joshi, P.V. Vibration Analysis of Partially Cracked Plate Submerged in Fluid. *J. Sound Vib.* **2018**, *412*, 28–57. [\[CrossRef\]](#)
127. Soni, S.; Jain, N.K.; Joshi, P.V.; Gupta, A.; Soni, S. Effect of Thermal Environment on Vibration Response of Partially Cracked Functionally Graded Plate Coupled with Fluid. *Mater. Today Proc.* **2018**, *5*, 27810–27819. [\[CrossRef\]](#)
128. Soni, S.; Jain, N.K.; Joshi, P.V. Effect of Thermal Environment on Vibration Analysis of Partially Cracked Thin Isotropic Plate Submerged in Fluid. *J. Solid Mech.* **2019**, *11*, 120–143. [\[CrossRef\]](#)
129. Soni, S.; Jain, N.K.; Joshi, P.V. Effect of Microstructure on Vibration Analysis of Partially Cracked Thin Orthotropic Plate Based on Strain Gradient Theory. In *AIP Conference Proceedings, Proceedings of the 1st International Conference on Advances in Mechanical Engineering and Nanotechnology (ICAMEN 2019), Jaipur, India, 8–9 March 2019*; American Institute of Physics Inc.: College Park, MD, USA, 2019; Volume 2148.
130. Soni, S.; Jain, N.K.; Joshi, P.V. Vibration and Deflection Analysis of Thin Cracked and Submerged Orthotropic Plate under Thermal Environment Using Strain Gradient Theory. *Nonlinear Dyn.* **2019**, *96*, 1575–1604. [\[CrossRef\]](#)
131. Soni, S.; Jain, N.K.; Joshi, P.V. Stability and Dynamic Analysis of Partially Cracked Thin Orthotropic Microplates under Thermal Environment: An Analytical Approach. *Mech. Based Des. Struct. Mach.* **2020**, *48*, 299–325. [\[CrossRef\]](#)
132. Mashrouteh, S.; Younesian, D.; Esmailzadeh, E. Multi-Resonance Analysis of a Viscoelastically Supported Orthotropic Plate with an Inclined Crack. *Nonlinear Dyn.* **2019**, *96*, 1717–1734. [\[CrossRef\]](#)
133. Ranjbaran, M.; Seifi, R. Analysis of Free Vibration of an Isotropic Plate with Surface or Internal Long Crack Using Generalized Differential Quadrature Method. *J. Strain. Anal. Eng. Des.* **2020**, *55*, 42–52. [\[CrossRef\]](#)
134. Dean, A.; Asur Vijaya Kumar, P.K.; Reinoso, J.; Gerendt, C.; Paggi, M.; Mahdi, E.; Rolfes, R. A Multi Phase-Field Fracture Model for Long Fiber Reinforced Composites Based on the Puck Theory of Failure. *Compos. Struct.* **2020**, *251*, 112446. [\[CrossRef\]](#)
135. Doan, D.H.; Van Do, T.; Nguyen, N.X.; Van Vinh, P.; Trung, N.T. Multi-Phase-Field Modelling of the Elastic and Buckling Behaviour of Laminates with Ply Cracks. *Appl. Math. Model.* **2021**, *94*, 68–86. [\[CrossRef\]](#)
136. Gonenli, C.; Das, O. Effect of Crack Location on Buckling and Dynamic Stability in Plate Frame Structures. *J. Braz. Soc. Mech. Sci. Eng.* **2021**, *43*, 311. [\[CrossRef\]](#)
137. Aftab, H.; Baneen, U.; Israr, A. Identification and Severity Estimation of a Breathing Crack in a Plate via Nonlinear Dynamics. *Nonlinear Dyn.* **2021**, *104*, 1973–1989. [\[CrossRef\]](#)
138. Nikkhoo, A.; Banihashemi, S.; Kiani, K. Parametric Investigations on Dynamics of Cracked Thin Rectangular Plates, Excited by a Moving Mass. *Sci. Iran.* **2022**, *30*, 860–876. [\[CrossRef\]](#)
139. Song, Y.; Xue, K.; Li, Q. A Solution Method for Free Vibration of Intact and Cracked Polygonal Thin Plates Using the Ritz Method and Jacobi Polynomials. *J. Sound Vib.* **2022**, *519*, 116578. [\[CrossRef\]](#)
140. Al-Shammari, M.A.; Husain, M.A.; Al-Waily, M. Free Vibration Analysis of Rectangular Plates with Cracked Holes. In *AIP Conference Proceedings, Proceedings of the 3rd International Scientific Conference of Alkafeel University (ISCKU 2021), Najaf, Iraq, 22–23 March 2021*; American Institute of Physics Inc.: College Park, MD, USA, 2022; Volume 2386.
141. Migot, A.; Naser, H.N.H.; Uglu, A.A.; Giurgiutiu, V. Investigations of Fatigue Crack Detection Using Local Vibration Techniques: Numerical and Experimental Studies. *J. Nondestruct. Eval.* **2023**, *42*, 12. [\[CrossRef\]](#)
142. Wang, Y.-S.; Shih, Y.-S. Analysis of the Vibration of a Cracked Ferromagnetic Rectangular Plate in a Transverse Magnetic Field. *J. Vib. Control.* **2023**, *29*, 2501–2514. [\[CrossRef\]](#)
143. Kou, S.; Zhang, X.; Li, W.; Song, C. Dynamic Response Parameter Analysis of Steel Frame Joints under Blast Loading. *Buildings* **2022**, *12*, 433. [\[CrossRef\]](#)
144. Cannon, L.; Cluble, S.K. Structural Response of Simple Partially-Clad Steel Frames to Long-Duration Blast Loading. *Structures* **2021**, *32*, 1260–1270. [\[CrossRef\]](#)

145. Yussof, M.M.; Silalahi, J.H.; Kamarudin, M.K.; Chen, P.-S.; Parke, G.A.R. Numerical Evaluation of Dynamic Responses of Steel Frame Structures with Different Types of Haunch Connection Under Blast Load. *Appl. Sci.* **2020**, *10*, 1815. [\[CrossRef\]](#)
146. Curry, R.J.; Langdon, G.S. Transient Response of Steel Plates Subjected to Close Proximity Explosive Detonations in Air. *Int. J. Impact Eng.* **2017**, *102*, 102–116. [\[CrossRef\]](#)
147. Wang, Z.; Gao, Y.; Zhang, Y.; Duan, Y.; Huang, C.; Wu, H. Analysis of Damage Characteristics of the Rectangular Steel Container under Near-Earth Explosion Loading. *Case Stud. Constr. Mater.* **2024**, *21*, e03518. [\[CrossRef\]](#)
148. Hu, Z.; Yang, Y.; Zhou, C.; Zheng, X.; Li, R. On the Symplectic Superposition Method for New Analytic Free Vibration Solutions of Side-Cracked Rectangular Thin Plates. *J. Sound Vib.* **2020**, *489*, 115695. [\[CrossRef\]](#)
149. Xue, J.; Wang, Y.; Chen, L. Nonlinear Vibration of Cracked Rectangular Mindlin Plate with In-Plane Preload. *J. Sound Vib.* **2020**, *481*, 115437. [\[CrossRef\]](#)
150. Das, O.; Gonenli, C.; Das, D.B. Crack Detection in Folded Plates with Back-Propagated Artificial Neural Network. *Steel Compos. Struct.* **2023**, *46*, 319–334. [\[CrossRef\]](#)
151. Bachene, M.; Tiberkak, R.; Rechak, S. Vibration Analysis of Cracked Plates Using the Extended Finite Element Method. *Arch. Appl. Mech.* **2009**, *79*, 249–262. [\[CrossRef\]](#)
152. Tran, L.V.; Ly, H.A.; Lee, J.; Wahab, M.A.; Nguyen-Xuan, H. Vibration Analysis of Cracked FGM Plates Using Higher-Order Shear Deformation Theory and Extended Isogeometric Approach. *Int. J. Mech. Sci.* **2015**, *96–97*, 65–78. [\[CrossRef\]](#)
153. Hu, Z.; Ni, Z.; An, D.; Chen, Y.; Li, R. Hamiltonian System-Based Analytical Solutions for the Free Vibration of Edge-Cracked Thick Rectangular Plates. *Appl. Math. Model.* **2023**, *117*, 451–478. [\[CrossRef\]](#)
154. Milazzo, A. Free Vibrations Analysis of Cracked Variable Stiffness Composite Plates by the EXtended Ritz Method. *Mech. Adv. Mater. Struct.* **2023**, *30*, 1675–1691. [\[CrossRef\]](#)
155. Li, T.Y.; Liu, J.X.; Zhang, T. Vibrational Power Flow Characteristics of Circular Plate Structures with Peripheral Surface Crack. *J. Sound Vib.* **2004**, *276*, 1081–1091. [\[CrossRef\]](#)
156. Rucka, M.; Wilde, K. Application of Continuous Wavelet Transform in Vibration Based Damage Detection Method for Beams and Plates. *J. Sound Vib.* **2006**, *297*, 536–550. [\[CrossRef\]](#)
157. Dwivedi, K.; Raza, A.; Pathak, H.; Talha, M.; Upadhyaya, R. Free Flexural Vibration of Cracked Composite Laminated Plate Using Higher-Order XFEM. *Eng. Fract. Mech.* **2023**, *289*, 109420. [\[CrossRef\]](#)
158. Wang, Y.; Wang, Z. Transverse Vibration of Viscoelastic Rectangular Plate with Linearly Varying Thickness and Multiple Cracks. *J. Sound Vib.* **2008**, *318*, 1005–1023. [\[CrossRef\]](#)
159. Phạm Minh, P. Analysis Free Vibration of the Functionally Grade Material Cracked Plates with Varying Thickness Using the Phase-Field Theory. *Transp. Commun. Sci. J.* **2019**, *70*, 122–131. [\[CrossRef\]](#)
160. Minh, P.P.; Duc, N.D. The Effect of Cracks on the Stability of the Functionally Graded Plates with Variable-Thickness Using HSDT and Phase-Field Theory. *Compos. B Eng.* **2019**, *175*, 107086. [\[CrossRef\]](#)
161. Pham Minh, P. Using Phase Field and Third-Order Shear Deformation Theory to Study the Effect of Cracks on Free Vibration of Rectangular Plates with Varying Thickness. *Transp. Commun. Sci. J.* **2020**, *71*, 853–867. [\[CrossRef\]](#)
162. Minh, P.P.; Duc, N.D. The Effect of Cracks and Thermal Environment on Free Vibration of FGM Plates. *Thin-Walled Struct.* **2021**, *159*, 107291. [\[CrossRef\]](#)
163. Minh, P.P.; Manh, D.T.; Duc, N.D. Free Vibration of Cracked FGM Plates with Variable Thickness Resting on Elastic Foundations. *Thin-Walled Struct.* **2021**, *161*, 107425. [\[CrossRef\]](#)
164. Le, M.; Lee, J. Ultrasonic Testing of Corrosion in Aircraft Rivet Using Spiking Neural Network. *J. Nondestruct. Eval.* **2023**, *42*, 78. [\[CrossRef\]](#)
165. Heo, J.; Yang, Z.; Xia, W.; Oterkus, S.; Oterkus, E. Free Vibration Analysis of Cracked Plates Using Peridynamics. *Ships Offshore Struct.* **2020**, *15*, S220–S229. [\[CrossRef\]](#)
166. Chandrakar, B.K.; Jain, N.K.; Gupta, A. Crack Orientation Effects on Vibration Characteristics of Bi-Directional Linearly Varying Thickness Partially Cracked Isotropic Micro-Plate: An Analytical Approach. *Springer Proc. Mater.* **2021**, *13*, 315–323. [\[CrossRef\]](#)
167. Le, V.A.; Nguyen, X.T. The Effect of Cracks on the Free Vibration of a Plate with Parabolic Thickness. *Eng. Technol. Appl. Sci. Res.* **2023**, *13*, 11100–11105. [\[CrossRef\]](#)
168. Adams, R.D.; Cawley, P.; Pye, C.J.; Stone, B.J. A Vibration Technique for Non-Destructively Assessing the Integrity of Structures. *J. Mech. Eng. Sci.* **1978**, *20*, 93–100. [\[CrossRef\]](#)
169. Lee, U.; Lesieutre, G.A.; Fang, L. Anisotropic Damage Mechanics Based on Strain Energy Equivalence and Equivalent Elliptical Microcracks. *Int. J. Solids Structures* **1997**, *34*, 4377–4397. [\[CrossRef\]](#)
170. Lee, U.; Kim, N.; Shin, J. Identification of Damages within a Plate Structure. In Proceedings of the 19th AIAA Applied Aerodynamics Conference, Anaheim, CA, USA, 1–14 June 2001; American Institute of Aeronautics and Astronautics Inc.: Reston, VA, USA, 2001.
171. Lee, U.; Cho, K.; Shin, J. Identification of Orthotropic Damages within a Thin Uniform Plate. *Int. J. Solids Struct.* **2003**, *40*, 2195–2213. [\[CrossRef\]](#)
172. Cornwell, P.; Doebling, S.W.; Farrar, C.R. Application of the Strain Energy Damage Detection Method to Plate-like Structures. *J. Sound Vib.* **1999**, *224*, 359–374. [\[CrossRef\]](#)
173. Li, Y.Y.; Cheng, L.; Yam, L.H.; Wong, W.O. Identification of Damage Locations for Plate-like Structures Using Damage Sensitive Indices: Strain Modal Approach. *Comput. Struct.* **2002**, *80*, 1881–1894. [\[CrossRef\]](#)

174. Wu, D.; Law, S.S. Damage Localization in Plate Structures from Flexibility and Its Derivatives. In Proceedings of the Smart Structures and Materials 2004: Sensors and Smart Structures Technologies for Civil, Mechanical, and Aerospace Systems, San Diego, CA, USA, 14–18 March 2004; SPIE: Bellingham, WA, USA, 2004; Volume 5391, p. 449.
175. Wu, D.; Law, S.S. Damage-Detection-Oriented Model for a Cracked Rectangular Plate. In Proceedings of the Smart Structures and Materials 2004: Sensors and Smart Structures Technologies for Civil, Mechanical, and Aerospace Systems, San Diego, CA, USA, 14–18 March 2004; SPIE: Bellingham, WA, USA, 2004; Volume 5391, p. 470.
176. Wu, D.; Law, S.S. Anisotropic Damage Model for an Inclined Crack in Thick Plate and Sensitivity Study for Its Detection. *Int. J. Solids Struct.* **2004**, *41*, 4321–4336. [\[CrossRef\]](#)
177. Wu, D.; Law, S.S. Damage Localization in Plate Structures from Uniform Load Surface Curvature. *J. Sound Vib.* **2004**, *276*, 227–244. [\[CrossRef\]](#)
178. Wu, D.; Law, S.S. Sensitivity of Uniform Load Surface Curvature for Damage Identification in Plate Structures. *J. Vib. Acoust. Trans. ASME* **2005**, *127*, 84–92. [\[CrossRef\]](#)
179. Wu, D.; Law, S.S. Crack Identification in Thin Plates with Anisotropic Damage Model and Vibration Measurements. *J. Appl. Mech. Trans. ASME* **2005**, *72*, 852–861. [\[CrossRef\]](#)
180. Yam, L.H.; Yan, Y.J.; Wei, Z. Vibration-Based Non Destructive Structural Damage Detection. *Key Eng. Mater.* **2004**, 270–273, 1446–1453. [\[CrossRef\]](#)
181. Yam, L.H.; Cheng, L.; Wei, Z.; Yan, Y.J. Damage Detection of Composite Structures Using Dynamic Analysis. *Key Eng. Mater.* **2005**, 295–296, 33–38. [\[CrossRef\]](#)
182. Huynh, D.; Tran, D. A Non-Destructive Crack Detection Technique Using Vibration Tests. In Proceedings of the Structural Integrity and Fracture International Conference (SIF'04), Brisbane, Australia, 26–29 September 2004; Atrons, A., Boland, J.N., Clegg, R., Griffiths, J.R., Eds.; The University of Queensland: Brisbane, Australia, 2004; pp. 155–162.
183. Huynh, D.; He, J.; Tran, D. Damage Location Vector: A Non-Destructive Structural Damage Detection Technique. *Comput. Struct.* **2005**, *83*, 2353–2367. [\[CrossRef\]](#)
184. Qiao, P.Z.; Lu, K.; Lestari, W. A Combined Static/Dynamic Technique for Damage Detection of Laminated Composite Plates. *Exp. Mech.* **2008**, *48*, 17–35. [\[CrossRef\]](#)
185. Ramos, L.F.; De Roeck, G.; Lourenço, P.B.; Campos-Costa, A. Damage Identification on Arched Masonry Structures Using Ambient and Random Impact Vibrations. *Eng. Struct.* **2010**, *32*, 146–162. [\[CrossRef\]](#)
186. Trana, D. Crack Detection in Structures Using Frequency Response Functions. In *AIP Conference Proceedings, Proceedings of the 2nd International Symposium on Computational Mechanics and the 12th International Conference on the Enhancement and Promotion of Computational Methods in Engineering and Science, Hong Kong, Macau, China, 30 November–3 December 2009*; American Institute of Physics Inc.: College Park, MD, USA, 2010; Volume 1233, pp. 1273–1278.
187. Xu, W.; Radzieński, M.; Ostachowicz, W.; Cao, M. Damage Detection in Plates Using Two-Dimensional Directional Gaussian Wavelets and Laser Scanned Operating Deflection Shapes. *Struct. Health Monit.* **2013**, *12*, 457–468. [\[CrossRef\]](#)
188. Fu, Y.Z.; Lu, Z.R.; Liu, J.K. Damage Identification in Plates Using Finite Element Model Updating in Time Domain. *J. Sound Vib.* **2013**, *332*, 7018–7032. [\[CrossRef\]](#)
189. Fu, Y.; Liu, J.; Wei, Z.; Lu, Z. A Two-Step Approach for Damage Identification in Plates. *J. Vib. Control.* **2016**, *22*, 3018–3031. [\[CrossRef\]](#)
190. Al-Agamy, M.; Abo-Elkhier, M.; Hamada, A.A.; Student, P.G. Damage Detection in Composite Plates Using Dynamic Response. *Int. J. Innov. Res. Sci.* **2019**, *8*, 1–15.
191. Huang, Y.-H.; Chen, J.-E.; Ge, W.-M.; Bian, X.-L.; Hu, W.-H. Research on Geometric Features of Phase Diagram and Crack Identification of Cantilever Beam with Breathing Crack. *Results Phys.* **2019**, *15*, 102561. [\[CrossRef\]](#)
192. Duvnjak, I.; Damjanović, D.; Bartolac, M.; Skender, A. Mode Shape-Based Damage Detection Method (MSDI): Experimental Validation. *Appl. Sci.* **2021**, *11*, 4589. [\[CrossRef\]](#)
193. Wei, Z.; Yam, L.H.; Cheng, L. NARMAX Model Representation and Its Application to Damage Detection for Multi-Layer Composites. *Compos. Struct.* **2005**, *68*, 109–117. [\[CrossRef\]](#)
194. Zhang, Y.; Wang, L.; Xiang, Z. Damage Detection by Mode Shape Squares Extracted from a Passing Vehicle. *J. Sound Vib.* **2012**, *331*, 291–307. [\[CrossRef\]](#)
195. Wei, Z.T.; Liu, J.K.; Lu, Z.R. Damage Identification in Plates Based on the Ratio of Modal Strain Energy Change and Sensitivity Analysis. *Inverse Probl. Sci. Eng.* **2016**, *24*, 265–283. [\[CrossRef\]](#)
196. De Castro, B.A.; Baptista, F.G.; Ciampa, F. Impedance-Based Structural Health Monitoring under Low Signal-to-Noise Ratio Conditions. In Proceedings of the 9th European Workshop on Structural Health Monitoring, Manchester, UK, 10–13 July 2018.
197. Yam, L.H.; Li, Y.Y.; Wong, W.O. Sensitivity Studies of Parameters for Damage Detection of Plate-like Structures Using Static and Dynamic Approaches. *Eng. Struct.* **2002**, *24*, 1465–1475. [\[CrossRef\]](#)
198. Zhang, Y.; Lie, S.T.; Xiang, Z. Damage Detection Method Based on Operating Deflection Shape Curvature Extracted from Dynamic Response of a Passing Vehicle. *Mech. Syst. Signal Process.* **2013**, *35*, 238–254. [\[CrossRef\]](#)
199. Alsaadi, A.; Shi, Y.; Jia, Y. Delamination Detection via Reconstructed Frequency Response Function of Composite Structures. In Proceedings of the 13th International Conference on Damage Assessment of Structures, Porto, Portugal, 9–10 July 2019; pp. 837–843.

200. Zhong, Y.; Yuan, S.; Qiu, L. Multiple Damage Detection on Aircraft Composite Structures Using Near-Field MUSIC Algorithm. *Sens. Actuators A Phys.* **2014**, *214*, 234–244. [\[CrossRef\]](#)
201. He, J.; Yuan, F.-G. Lamb Wave-Based Subwavelength Damage Imaging Using the DORT-MUSIC Technique in Metallic Plates. *Struct. Health Monit.* **2016**, *15*, 65–80. [\[CrossRef\]](#)
202. Katunin, A. Damage Identification in Composite Plates Using Two-Dimensional B-Spline Wavelets. *Mech. Syst. Signal Process.* **2011**, *25*, 3153–3167. [\[CrossRef\]](#)
203. Cao, M.S.; Ostachowicz, W.; Bai, R.B.; Radziński, M. Fractal Mechanism for Characterizing Singularity of Mode Shape for Damage Detection. *Appl. Phys. Lett.* **2013**, *103*, 221906. [\[CrossRef\]](#)
204. Huang, T.; Schröder, K.-U. A Bayesian Probabilistic Approach for Damage Identification in Plate Structures Using Responses at Vibration Nodes. *Mech. Syst. Signal Process.* **2021**, *146*, 106998. [\[CrossRef\]](#)
205. Zuo, H.; Yang, Z.; Xu, C.; Tian, S.; Chen, X. Damage Identification for Plate-like Structures Using Ultrasonic Guided Wave Based on Improved MUSIC Method. *Compos. Struct.* **2018**, *203*, 164–171. [\[CrossRef\]](#)
206. Reddy, D.M.; Swarnamani, S. Application of the FRF Curvature Energy Damage Detection Method to Plate like Structures. *World J. Model. Simul.* **2012**, *8*, 147–153.
207. Rouquand, A.; Pontiroli, C.; Canton, E. An Explicit Damage Model for Dynamic Concrete Behaviour. In *Numerical Simulations and Comparisons with Experimental Results on Reinforced Concrete Plates under Blast Loading*; WIT Press: Cambridge, MA, USA, 1996; Volume 22.
208. Ivančević, D.; Smojver, I. Explicit Multiscale Modelling of Impact Damage on Laminated Composites—Part II: Multiscale Analyses. *Compos. Struct.* **2016**, *145*, 259–268. [\[CrossRef\]](#)
209. Kim, E.-H.; Rim, M.-S.; Lee, I.; Hwang, T.-K. Composite Damage Model Based on Continuum Damage Mechanics and Low Velocity Impact Analysis of Composite Plates. *Compos. Struct.* **2013**, *95*, 123–134. [\[CrossRef\]](#)
210. Maire, J.-F.; Lesne, P.-M. An Explicit Damage Model for the Design of Composites Structures. *Compos. Sci. Technol.* **1998**, *58*, 773–778. [\[CrossRef\]](#)
211. Moreau, K.; Moës, N.; Picart, D.; Stainier, L. Explicit Dynamics with a Non-Local Damage Model Using the Thick Level Set Approach. *Int. J. Numer. Methods Eng.* **2015**, *102*, 808–838. [\[CrossRef\]](#)
212. Zhou, Y.; Yazdani Nezhad, H.; Hou, C.; Wan, X.; McCarthy, C.T.; McCarthy, M.A. A Three Dimensional Implicit Finite Element Damage Model and Its Application to Single-Lap Multi-Bolt Composite Joints with Variable Clearance. *Compos. Struct.* **2015**, *131*, 1060–1072. [\[CrossRef\]](#)
213. César de Sá, J.M.A.; Areias, P.M.A.; Zheng, C. Damage Modelling in Metal Forming Problems Using an Implicit Non-Local Gradient Model. *Comput. Methods Appl. Mech. Eng.* **2006**, *195*, 6646–6660. [\[CrossRef\]](#)
214. Seupel, A.; Hütter, G.; Kuna, M. An Efficient FE-Implementation of Implicit Gradient-Enhanced Damage Models to Simulate Ductile Failure. *Eng. Fract. Mech.* **2018**, *199*, 41–60. [\[CrossRef\]](#)
215. Tran, H.T.; Bui, T.Q.; Chijiwa, N.; Hirose, S. A New Implicit Gradient Damage Model Based on Energy Limiter for Brittle Fracture: Theory and Numerical Investigation. *Comput. Methods Appl. Mech. Eng.* **2023**, *413*, 116123. [\[CrossRef\]](#)
216. Kurtaran, H. Shape Effect on Free Vibration of Functionally Graded Plates. *Int. J. Eng. Appl. Sci.* **2014**, *6*, 52. [\[CrossRef\]](#)
217. Wang, F.; Chan, T. Review of Vibration-Based Damage Detection and Condition Assessment of Bridge Structures Using Structural Health Monitoring. In *Proceedings of The Second Infrastructure Theme Postgraduate Conference: Rethinking Sustainable Development-Planning, Infrastructure Engineering, Design and Managing Urban Infrastructure*; Queensland University of Technology: Brisbane, Australia, 2009; pp. 35–47.
218. Yang, Z.; Chen, X.; Yu, J.; Liu, R.; Liu, Z.; He, Z. A Damage Identification Approach for Plate Structures Based on Frequency Measurements. *Nondestruct. Test. Eval.* **2013**, *28*, 321–341. [\[CrossRef\]](#)
219. Xu, Y.; Zhu, W. Non-Model-Based Damage Identification of Plates Using Measured Mode Shapes. *Struct. Health Monit.* **2017**, *16*, 3–23. [\[CrossRef\]](#)
220. Beskhyroun, S.; Wegner, L.D.; Sparling, B.F. New Methodology for the Application of Vibration-Based Damage Detection Techniques. *Struct. Control. Health Monit.* **2012**, *19*, 632–649. [\[CrossRef\]](#)
221. Catbas, F.N.; Brown, D.L.; Aktan, A.E. Use of Modal Flexibility for Damage Detection and Condition Assessment: Case Studies and Demonstrations on Large Structures. *J. Struct. Eng.* **2006**, *132*, 1699–1712. [\[CrossRef\]](#)
222. Pandey, A.K.; Biswas, M. Experimental Verification of Flexibility Difference Method for Locating Damage in Structures. *J. Sound Vib.* **1995**, *184*, 311–328. [\[CrossRef\]](#)
223. Abdel wahab, M.M.; De roeck, G. Damage Detection in Bridges Using Modal Curvatures: Application to a Real Damage Scenario. *J. Sound Vib.* **1999**, *226*, 217–235. [\[CrossRef\]](#)
224. Shi, Z.Y.; Law, S.S.; Zhang, L.M. Structural Damage Detection from Modal Strain Energy Change. *J. Eng. Mech.* **2000**, *126*, 1216–1223. [\[CrossRef\]](#)
225. Hu, H.; Wang, B.-T.; Lee, C.-H.; Su, J.-S. Damage Detection of Surface Cracks in Composite Laminates Using Modal Analysis and Strain Energy Method. *Compos. Struct.* **2006**, *74*, 399–405. [\[CrossRef\]](#)
226. Meruane, V.; Lasen, M.; López Droguett, E.; Ortiz-Bernardin, A. Modal Strain Energy-Based Debonding Assessment of Sandwich Panels Using a Linear Approximation with Maximum Entropy. *Entropy* **2017**, *19*, 619. [\[CrossRef\]](#)
227. Siow, P.Y.; Ong, Z.C.; Khoo, S.Y.; Lim, K.-S. Damage Sensitive PCA-FRF Feature in Unsupervised Machine Learning for Damage Detection of Plate-like Structures. *Int. J. Struct. Stab. Dyn.* **2021**, *21*, 2150028. [\[CrossRef\]](#)

228. Zhao, M.; Zhou, W.; Huang, Y.; Li, H. Sparse Bayesian Learning Approach for Propagation Distance Recognition and Damage Localization in Plate-like Structures Using Guided Waves. *Struct. Health Monit.* **2021**, *20*, 3–24. [\[CrossRef\]](#)
229. Lu, Z.R.; Law, S.S. Identification of System Parameters and Input Force from Output Only. *Mech. Syst. Signal Process.* **2007**, *21*, 2099–2111. [\[CrossRef\]](#)
230. Zimmerman, D.C.; Kaouk, M. Structural Damage Detection Using a Minimum Rank Update Theory. *J. Vib. Acoust.* **1994**, *116*, 222–231. [\[CrossRef\]](#)
231. Messina, A.; Williams, E.J.; Contursi, T. Structural Damage Detection by a Sensitivity and Statistical-Based Method. *J. Sound Vib.* **1998**, *216*, 791–808. [\[CrossRef\]](#)
232. Wang, Q.P.; Guo, X.; Wang, H.X. Application of Damage Location Vector Method in Structural Damage Identification. In Proceedings of the Road Materials and New Innovations in Pavement Engineering, American Society of Civil Engineers, Reston, VA, USA, 23 May 2011; pp. 136–143.
233. Nguyen-Thoi, T.; Tran-Viet, A.; Nguyen-Minh, N.; Vo-Duy, T.; Ho-Huu, V. A Combination of Damage Locating Vector Method (DLV) and Differential Evolution Algorithm (DE) for Structural Damage Assessment. *Front. Struct. Civ. Eng.* **2018**, *12*, 92–108. [\[CrossRef\]](#)
234. Jepsen, M.; Ulriksen, M.D.; Bernal, D. Closed-Loop Damage-Locating Vectors. In *European Workshop on Structural Health Monitoring*; Springer: Cham, Switzerland, 2023; pp. 697–707.
235. Gao, Y.; Spencer, B.F.; Bernal, D. Experimental Verification of the Damage Locating Vector Method. *J. Eng. Mech.* **2004**, *133*.
236. Bernal, D.; Gunes, B. Flexibility Based Approach for Damage Characterization: Benchmark Application. *J. Eng. Mech.* **2004**, *130*, 61–70. [\[CrossRef\]](#)
237. Bernal, D. Load Vectors for Damage Localization. *J. Eng. Mech.* **2002**, *128*, 7–14. [\[CrossRef\]](#)
238. Cheng, C.; Nie, Z.H.; Ma, H.W. Structural Damage Detection of the Simple Beam Based on Responses Phase Space. *Adv. Mat. Res.* **2012**, *605–607*, 989–995. [\[CrossRef\]](#)
239. Zhang, W.; Ma, H.; Zeng, J.; Wu, S.; Wen, B. Vibration Responses Analysis of an Elastic-Support Cantilever Beam with Crack and Offset Boundary. *Mech. Syst. Signal Process.* **2017**, *95*, 205–218. [\[CrossRef\]](#)
240. Rezaee, M.; Shaterian-Alghalandis, V. A New Crack Detection Method in a Beam under Geometrically Nonlinear Vibration. *Arch. Appl. Mech.* **2018**, *88*, 1491–1506. [\[CrossRef\]](#)
241. Wang, J.; Zhang, J.; Yao, Z.; Yang, X.; Sun, R.; Zhao, Y. Nonlinear Characteristics of a Multi-Degree-of-Freedom Spur Gear System with Bending-Torsional Coupling Vibration. *Mech. Syst. Signal Process.* **2019**, *121*, 810–827. [\[CrossRef\]](#)
242. Andreaus, U.; Baragatti, P. Cracked Beam Identification by Numerically Analysing the Nonlinear Behaviour of the Harmonically Forced Response. *J. Sound Vib.* **2011**, *330*, 721–742. [\[CrossRef\]](#)
243. Andreaus, U.; Baragatti, P. Experimental Damage Detection of Cracked Beams by Using Nonlinear Characteristics of Forced Response. *Mech. Syst. Signal Process.* **2012**, *31*, 382–404. [\[CrossRef\]](#)
244. Bovsunovsky, A.P.; Surace, C. Considerations Regarding Superharmonic Vibrations of a Cracked Beam and the Variation in Damping Caused by the Presence of the Crack. *J. Sound Vib.* **2005**, *288*, 865–886. [\[CrossRef\]](#)
245. Bovsunovsky, A.P.; Bovsunovsky, O. Crack Detection in Beams by Means of the Driving Force Parameters Variation at Non-Linear Resonance Vibrations. *Key Eng. Mater.* **2007**, *347*, 413–420. [\[CrossRef\]](#)
246. Douka, E.; Hadjileontiadis, L.J. Time–Frequency Analysis of the Free Vibration Response of a Beam with a Breathing Crack. *NDT E Int.* **2005**, *38*, 3–10. [\[CrossRef\]](#)
247. Alexandrino, P.D.S.L.; Gomes, G.F.; Cunha, S.S. A Robust Optimization for Damage Detection Using Multiobjective Genetic Algorithm, Neural Network and Fuzzy Decision Making. *Inverse Probl. Sci. Eng.* **2020**, *28*, 21–46. [\[CrossRef\]](#)
248. Tan, Z.X.; Thambiratnam, D.P.; Chan, T.H.T.; Gordan, M.; Abdul Razak, H. Damage Detection in Steel-Concrete Composite Bridge Using Vibration Characteristics and Artificial Neural Network. *Struct. Infrastruct. Eng.* **2020**, *16*, 1247–1261. [\[CrossRef\]](#)
249. Padil, K.H.; Bakhary, N.; Abdulkareem, M.; Li, J.; Hao, H. Non-Probabilistic Method to Consider Uncertainties in Frequency Response Function for Vibration-Based Damage Detection Using Artificial Neural Network. *J. Sound Vib.* **2020**, *467*, 115069. [\[CrossRef\]](#)
250. Nasiri, M.R.; Mahjoob, M.J.; Aghakasiri, A. Damage Detection in a Composite Plate Using Modal Analysis and Artificial Intelligence. *Appl. Compos. Mater.* **2011**, *18*, 513–520. [\[CrossRef\]](#)
251. Yam, L.H.; Yan, Y.J.; Jiang, J.S. Vibration-Based Damage Detection for Composite Structures Using Wavelet Transform and Neural Network Identification. *Compos. Struct.* **2003**, *60*, 403–412. [\[CrossRef\]](#)

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.



DSPACE

<https://dspace.org/>

Fundamental challenges and complexities of damage identification from dynamic response in plate structures

Alshammari, Yousef Lafi A.; He, Feiyang; Alrwili, Abdullah Ayed; Khan, Muhammad

2024-09-02

MDPI

<https://doi.org/10.3390/app14188230>

Alshammari YLA, He F, Alrwili AA, Khan M. (2024) Fundamental challenges and complexities of damage identification from dynamic response in plate structures. Applied Sciences, Volume 14, Issue 18, September 2024, pp. 8230-8230